

屋内照明器具特性	
品番 (品名)	XLX210PENJ
光源	LED5000_85_1550 ×1 1550.0 lm
管理番号	K0137984 (*) DB 1
BZ分類	BZ5/4.5/BZ4/6.0/BZ5/8.5/BZ4

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																				Z C M	
下方光束				1 0 0 %																					
保守率		良 中 否	0 . 8 1	0 . 6	5 7	4 5	3 7	3 1	5 5	4 4	3 6	3 1	5 3	4 3	3 6	3 1	5 1	4 2	3 6	3 1	2 9				
			0 . 7 7	0 . 8	6 7	5 5	4 8	4 2	6 5	5 5	4 7	4 2	6 3	5 3	4 6	4 1	6 0	5 2	4 6	4 1	3 9				
			0 . 6 8	1 . 0	7 4	6 3	5 5	4 9	7 2	6 2	5 5	4 9	6 9	6 0	5 4	4 9	6 6	5 9	5 3	4 9	4 6				
				1 . 2 5	8 0	7 0	6 3	5 7	7 8	6 9	6 2	5 7	7 5	6 7	6 1	5 6	7 2	6 6	6 0	5 6	5 4				
下方投影面積		c m ²	1 . 5	8 4	7 5	6 8	6 3	8 2	7 4	6 8	6 3	7 9	7 2	6 7	6 2	7 6	7 0	6 5	6 1	5 9					
等価発光面積			c m ²	2 . 0	9 0	8 2	7 6	7 1	8 8	8 1	7 6	7 1	8 5	7 9	7 4	7 0	8 2	7 7	7 3	6 9	6 7				
取付 高さ	器具間隔最大限			2 . 5	9 3	8 7	8 2	7 7	9 1	8 6	8 1	7 7	8 8	8 4	7 9	7 6	8 6	8 2	7 8	7 5	7 2				
	横方向 (A)		縦方向 (B)		3 . 0	9 6	9 0	8 6	8 2	9 4	8 9	8 5	8 1	9 1	8 7	8 3	8 0	8 8	8 5	8 2	7 9	7 6			
1 . 5m	1 . 9 1 m	1 . 9 5 m	4 . 0	9 9	9 4	9 1	8 7	9 7	9 3	9 0	8 7	9 4	9 1	8 8	8 5	9 2	8 9	8 6	8 4	8 1					
2	2 . 5 4	2 . 5 6	5 . 0	1 0 1	9 7	9 4	9 1	9 9	9 6	9 3	9 0	9 6	9 4	9 1	8 9	9 4	9 1	8 9	8 7	8 5					
2 . 5	3 . 1 7	3 . 1 8	7 . 0	1 0 3	1 0 0	9 8	9 6	1 0 1	9 9	9 7	9 5	9 9	9 7	9 5	9 3	9 6	9 5	9 3	9 1	8 9					
3	3 . 8 1	3 . 8	1 0 . 0	1 0 4	1 0 3	1 0 1	9 9	1 0 3	1 0 1	1 0 0	9 8	1 0 0	9 9	9 8	9 6	9 8	9 7	9 6	9 5	9 2					

