

# 屋内照明器具特性

品番 (品名)	XND1039SL									
光源	LED3000_85_970 x1					970.0 lm				
管理番号	K0176073(0)DB1									
BZ分類	BZ1									

器具効率	100%	天井	80%				70%				50%				30%				0%				
	上方光束		0%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
	下方光束		100%		床	10%				10%				10%				10%				0%	
室指数	照明率 ( X0.01 )																			ZCM			
保守率	良	0.81	0.6	73	65	60	56	73	65	60	56	71	64	59	56	69	63	59	56	54			
	中	0.77	0.8	83	75	70	67	82	75	70	67	80	74	70	66	78	73	69	66	65			
	否	0.68	1.0	88	82	77	74	87	81	77	74	85	80	76	73	83	79	75	73	71			
			1.25	92	87	83	80	91	86	82	79	89	85	82	79	87	84	81	78	77			
下方投影面積			c m <sup>2</sup>																				
	等価発光面積			c m <sup>2</sup>																			
取付高さ	器具間隔最大限																						
	横方向 (A)	縦方向 (B)																					
H m	1.09 H m	1.09 H m	4.0	104	101	99	98	102	100	99	97	100	99	97	96	99	97	96	98	97	96	94	92
			5.0	105	103	101	100	103	102	100	99	101	100	99	97	99	97	99	98	97	96	94	92
			7.0	106	104	103	102	105	103	102	101	102	101	100	99	100	99	99	99	98	97	95	93
			10.0	107	106	105	104	105	104	104	103	103	102	102	101	101	100	100	99	99	97	95	93

