

屋内照明器具特性	
品番 (品名)	X F L 3 1 2 T C B
光源	LDL40S. N / 14 / 26 (2600A) ×1 2600.0 lm
管理番号	K0126758 (1) DR 1
BZ分類	BZ4 / 0.7 / BZ3 / 1.8 / BZ4

器具効率		83 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束		0 %		床	10 %				10 %				10 %				10 %				0 %
下方光束		83 %		室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.81	0.6	51	41	35	31	50	41	35	31	48	40	35	31	46	39	34	31	29
			0.77	0.8	59	50	45	40	58	50	44	40	56	49	44	40	54	48	43	40	38
			0.68	1.0	64	57	51	47	63	56	51	47	61	55	50	46	59	54	49	46	44
				1.25	69	62	57	53	68	61	57	53	66	60	56	52	64	59	55	52	50
下方投影面積		cm ²	1.5	72	66	61	57	71	65	61	57	69	64	60	56	67	62	59	56	54	
等価発光面積		cm ²	2.0	76	71	67	63	75	70	66	63	73	69	65	62	71	67	64	62	60	
取付 高さ	器具間隔最大限		2.5	79	75	71	68	78	74	70	67	76	72	69	66	73	70	68	66	64	
	横方向 (A) 縦方向 (B)		3.0	81	77	74	71	80	76	73	70	77	74	72	69	75	73	70	68	66	
1.5m	2.03 m	2.05 m	4.0	83	80	77	75	82	79	77	74	80	77	75	73	78	76	74	72	70	
2	2.69	2.56	5.0	84	82	80	77	83	81	79	77	81	79	77	76	79	77	76	74	72	
2.5	3.34	3.1	7.0	86	84	82	81	85	83	81	80	83	81	80	79	81	79	78	77	75	
3	3.99	3.65	10.0	87	86	84	83	86	85	84	82	84	83	82	81	82	81	80	79	77	

