

屋内照明器具特性	
品番 (品名)	X F L 3 1 2 T E X
光源	LDL40S. N/14/26(2600A) ×1 2600.0 lm
管理番号	K0126416 (1) DB1
BZ分類	BZ3/0.7/BZ2/8.5/BZ1

器具効率		71 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.81	0.6	47	39	35	32	46	39	35	32	45	38	34	31	43	38	34	31	30
			0.77	0.8	55	49	44	41	54	48	44	41	52	47	44	41	51	47	43	41	39
			0.68	1.0	60	54	50	47	59	54	50	47	57	53	49	47	56	52	49	47	45
				1.25	63	59	55	52	63	58	55	52	61	57	54	52	59	56	54	51	50
下方投影面積		cm ²		1.5	66	62	58	56	65	61	58	56	63	60	57	55	62	59	57	55	53
			等価発光面積	cm ²	2.0	69	65	63	60	68	65	62	60	66	64	61	59	65	62	61	59
取付 高さ	器具間隔最大限			2.5	71	68	65	63	70	67	65	63	68	66	64	62	66	65	63	62	60
	横方向 (A) 縦方向 (B)			3.0	72	69	67	65	71	69	67	65	69	67	66	64	68	66	65	63	62
1.5m	2.4 m	2.1 m		4.0	73	71	70	68	72	71	69	68	71	69	68	67	69	68	67	66	64
2	3.2	2.66		5.0	74	72	71	70	73	72	70	69	71	70	69	68	70	69	68	67	65
2.5	3.98	3.23		7.0	75	74	73	72	74	73	72	71	72	71	71	70	71	70	69	69	67
3	4.74	3.81		10.0	76	75	74	73	75	74	73	73	73	72	72	71	71	71	71	70	68

