

屋内照明器具特性	
品番 (品名)	X F L 3 1 2 T E Y
光源	LDL40S. N/ 14/ 26 (2600A) ×1 2600.0 lm
管理番号	K0126447 (1) DB 1
BZ分類	BZ3/ 0.7/ BZ2/ 8.5/ BZ1

器具効率		70 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束		0 %		床	10 %				10 %				10 %				10 %				0 %
下方光束		70 %	室指数	照明率 (X0.01) Z CM																	
保守率		良	0.81	0.6	46	38	34	31	45	38	34	31	43	37	33	31	42	37	33	31	29
		中	0.77	0.8	53	47	43	40	53	47	43	40	51	46	42	40	50	45	42	40	38
		否	0.68	1.0	58	53	49	46	57	52	49	46	56	51	48	46	54	51	48	45	44
				1.25	62	57	54	51	61	57	53	51	59	56	53	50	58	55	52	50	49
下方投影面積		cm ²		1.5	64	60	57	54	63	59	56	54	62	58	56	54	60	57	55	53	52
等価発光面積		cm ²		2.0	67	64	61	59	66	63	61	59	64	62	60	58	63	61	59	57	56
取付	器具間隔最大限			2.5	69	66	64	62	68	65	63	61	66	64	62	61	65	63	61	60	58
高さ	横方向 (A)		縦方向 (B)	3.0	70	67	65	64	69	67	65	63	67	66	64	62	66	64	63	62	60
1.5m	2.38 m	2.1 m	4.0	71	69	68	66	70	69	67	66	69	67	66	65	67	66	65	64	62	
2	3.18	2.66	5.0	72	71	69	68	71	70	69	67	70	68	67	66	68	67	66	65	64	
2.5	3.96	3.24	7.0	73	72	71	70	72	71	70	69	71	70	69	68	69	68	68	67	65	
3	4.73	3.83	10.0	74	73	72	71	73	72	71	71	71	71	70	70	70	69	69	68	66	

