

# 屋内照明器具特性

品番 (品名)	XFL319CV																
光源	LDL40S.N/29/38(3800A) ×1 3800.0lm																
管理番号	K0126222(*)DB1																
BZ分類	BZ5/4.5/BZ4																

器具効率	94%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	0%	室指数	照明率 (X0.01) ZCM																		
下方光束	94%																				
保守率	良 0.9 中 0.86 否 0.76	0.6	5.2	4.1	3.3	2.8	5.1	4.0	3.3	2.8	4.9	3.9	3.2	2.8	4.7	3.8	3.2	2.8	2.6		
		0.8	6.2	5.1	4.3	3.8	6.1	5.0	4.3	3.8	5.8	4.9	4.2	3.8	5.6	4.8	4.2	3.7	3.5		
		1.0	6.8	5.8	5.1	4.5	6.7	5.7	5.0	4.5	6.4	5.6	5.0	4.5	6.2	5.4	4.9	4.4	4.2		
		1.25	7.4	6.5	5.8	5.3	7.3	6.4	5.8	5.3	7.0	6.3	5.7	5.2	6.7	6.1	5.6	5.2	5.0		
下方投影面積	c m <sup>2</sup>	1.5	7.9	7.0	6.4	5.8	7.7	6.9	6.3	5.8	7.4	6.7	6.2	5.8	7.1	6.6	6.1	5.7	5.5		
		2.0	8.4	7.7	7.2	6.7	8.3	7.6	7.1	6.6	8.0	7.4	7.0	6.6	7.7	7.2	6.8	6.5	6.3		
取付高さ	器具間隔最大限		2.5	8.7	8.2	7.7	7.2	8.6	8.1	7.6	7.2	8.3	7.9	7.5	7.1	8.1	7.7	7.3	7.0	6.8	
	横方向 (A)	縦方向 (B)	3.0	9.0	8.5	8.0	7.7	8.8	8.4	8.0	7.6	8.6	8.2	7.8	7.5	8.3	8.0	7.7	7.4	7.2	
1.5m	2.17m	2.16m	4.0	9.3	8.9	8.5	8.2	9.1	8.8	8.4	8.2	8.9	8.6	8.3	8.0	8.6	8.4	8.1	7.9	7.7	
2	2.87	2.73	5.0	9.5	9.1	8.8	8.6	9.3	9.0	8.7	8.5	9.1	8.8	8.6	8.4	8.8	8.6	8.4	8.2	8.0	
2.5	3.57	3.3	7.0	9.7	9.4	9.2	9.0	9.5	9.3	9.1	8.9	9.3	9.1	8.9	8.8	9.1	8.9	8.8	8.6	8.3	
3	4.25	3.89	10.0	9.8	9.6	9.5	9.3	9.7	9.5	9.4	9.2	9.5	9.3	9.2	9.1	9.2	9.1	9.0	8.9	8.6	

