

屋内照明器具特性	
品番 (品名)	X L Y 1 2 0 H G
光源	L E D 9 9 9 9 _ 8 0 _ 1 6 8 0 × 1 1 6 8 0 . 0 l m
管理番号	K 0 1 6 2 6 7 8 (0) D 1
B Z 分類	B Z 5

器具効率		1 0 0 %		反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
					壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
					床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
					室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 7 8	0 . 6	5 5	4 2	3 4	2 9	5 3	4 1	3 4	2 9	5 0	4 0	3 3	2 8	4 7	3 8	3 2	2 8	2 5	
			0 . 7 6	0 . 8	6 4	5 3	4 4	3 9	6 3	5 1	4 4	3 8	5 9	5 0	4 3	3 8	5 6	4 8	4 2	3 7	3 4	
			0 . 7 2	1 . 0	7 1	6 0	5 2	4 6	6 9	5 8	5 1	4 5	6 5	5 6	5 0	4 4	6 2	5 4	4 8	4 4	4 1	
				1 . 2 5	7 7	6 6	5 9	5 3	7 5	6 5	5 8	5 2	7 1	6 3	5 6	5 1	6 7	6 0	5 5	5 0	4 7	
下方投影面積		c m ²	1 . 5	8 1	7 1	6 4	5 8	7 9	7 0	6 3	5 8	7 5	6 7	6 1	5 6	7 1	6 5	6 0	5 5	5 2		
			等価発光面積	c m ²	2 . 0	8 6	7 8	7 2	6 6	8 4	7 7	7 1	6 6	8 0	7 4	6 9	6 4	7 6	7 1	6 7	6 3	5 9
取付 高さ	器具間隔最大限			2 . 5	9 0	8 3	7 7	7 2	8 8	8 1	7 6	7 1	8 4	7 8	7 4	7 0	8 0	7 5	7 1	6 8	6 4	
	横方向 (A)		縦方向 (B)	3 . 0	9 3	8 6	8 1	7 7	9 0	8 5	8 0	7 6	8 6	8 2	7 7	7 4	8 2	7 9	7 5	7 2	6 8	
1 . 5 m	1 . 9 8 m	2 . 1 1 m	4 . 0	9 6	9 1	8 6	8 2	9 4	8 9	8 5	8 1	9 0	8 6	8 2	7 9	8 6	8 3	8 0	7 7	7 3		
2	2 . 6 1	2 . 6 6	5 . 0	9 8	9 4	9 0	8 6	9 6	9 2	8 8	8 5	9 2	8 9	8 6	8 3	8 8	8 5	8 3	8 1	7 6		
2 . 5	3 . 2 5	3 . 2 3	7 . 0	1 0 0	9 7	9 4	9 1	9 8	9 5	9 3	9 0	9 4	9 2	9 0	8 7	9 1	8 9	8 7	8 5	8 1		
3	3 . 8 8	3 . 8 1	1 0 . 0	1 0 2	1 0 0	9 7	9 5	1 0 0	9 8	9 6	9 4	9 6	9 5	9 3	9 1	9 3	9 1	9 0	8 8	8 4		

