

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | XLX230DEN C                  |
| 光源       | LED5000_85_3200 ×1 3200.0 lm |
| 管理番号     | K0130919 (＊) DB 1            |
| BZ分類     | BZ5                          |

| 器具効率     |           | 100 %           | 反射率       | 天井            | 80 %            |     |    |     | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |    |    |   |   |
|----------|-----------|-----------------|-----------|---------------|-----------------|-----|----|-----|------|----|----|----|------|----|----|----|------|----|----|----|-----|----|----|---|---|
|          |           |                 |           | 壁             | 70              | 50  | 30 | 10  | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |    |    |   |   |
|          |           |                 |           | 床             | 10 %            |     |    |     | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |    |    |   |   |
| 上方光束     |           | 4 %             | 室指数       | 照明率 ( X0.01 ) |                 |     |    |     |      |    |    |    |      |    |    |    |      |    |    |    |     |    | Z  | C | M |
| 下方光束     |           | 96 %            |           |               |                 |     |    |     |      |    |    |    |      |    |    |    |      |    |    |    |     |    |    |   |   |
| 保守率      |           | 良<br>中<br>否     | 0.83      | 0.6           | 55              | 42  | 34 | 29  | 53   | 42 | 34 | 29 | 51   | 40 | 33 | 28 | 48   | 39 | 33 | 28 | 26  |    |    |   |   |
|          |           |                 | 0.81      | 0.8           | 65              | 53  | 45 | 39  | 63   | 52 | 44 | 38 | 60   | 50 | 43 | 38 | 57   | 48 | 42 | 37 | 35  |    |    |   |   |
|          |           |                 | 0.77      | 1.0           | 71              | 60  | 52 | 46  | 69   | 59 | 51 | 46 | 66   | 57 | 50 | 45 | 62   | 55 | 49 | 44 | 42  |    |    |   |   |
|          |           |                 |           | 1.25          | 77              | 67  | 59 | 53  | 75   | 66 | 58 | 53 | 71   | 63 | 57 | 52 | 68   | 61 | 56 | 51 | 48  |    |    |   |   |
| 下方投影面積   |           | cm <sup>2</sup> |           | 1.5           | 81              | 72  | 65 | 59  | 79   | 70 | 64 | 58 | 75   | 68 | 62 | 57 | 72   | 66 | 60 | 56 | 53  |    |    |   |   |
|          |           |                 | 等価発光面積    |               | cm <sup>2</sup> | 2.0 | 87 | 79  | 72   | 67 | 85 | 77 | 71   | 66 | 81 | 75 | 69   | 65 | 77 | 72 | 68  | 64 | 60 |   |   |
| 取付<br>高さ | 器具間隔最大限   |                 | 2.5       | 90            | 84              | 78  | 73 | 88  | 82   | 77 | 72 | 85 | 79   | 74 | 70 | 81 | 76   | 72 | 69 | 66 |     |    |    |   |   |
|          | 横方向 ( A ) |                 | 縦方向 ( B ) |               | 3.0             | 93  | 87 | 82  | 77   | 91 | 85 | 80 | 76   | 87 | 82 | 78 | 75   | 84 | 80 | 76 | 73  | 69 |    |   |   |
| 1.5m     | 1.94 m    | 1.96 m          | 4.0       | 96            | 91              | 87  | 83 | 94  | 90   | 86 | 82 | 91 | 87   | 83 | 80 | 87 | 84   | 81 | 78 | 75 |     |    |    |   |   |
| 2        | 2.58      | 2.58            | 5.0       | 98            | 94              | 90  | 87 | 96  | 93   | 89 | 86 | 93 | 89   | 86 | 84 | 89 | 87   | 84 | 82 | 78 |     |    |    |   |   |
| 2.5      | 3.23      | 3.2             | 7.0       | 101           | 97              | 95  | 92 | 99  | 96   | 93 | 91 | 95 | 93   | 90 | 88 | 92 | 90   | 88 | 86 | 82 |     |    |    |   |   |
| 3        | 3.89      | 3.83            | 10.0      | 102           | 100             | 98  | 96 | 101 | 99   | 96 | 95 | 97 | 95   | 94 | 92 | 94 | 92   | 91 | 90 | 86 |     |    |    |   |   |

