

屋内照明器具特性

品番 (品名)	XLF213NNN(JYOUJI_CEILING)	
光源	LED5000_85_1550 ×1	1550.0 lm
管理番号	K0153232(4)DB1	
BZ分類	BZ6/0.7/BZ5/3.5/BZ6/4.5/BZ5/6.0/BZ6	

器具効率	100%	天井	80%				70%				50%				30%				0%					
	上方光束 9%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%				
下方光束	91%	床		10%				10%				10%				10%				0%				
室指数	照明率 (X0.01)																				ZCM			
保守率	良	0.83	0.6	53	41	33	27	52	40	32	27	48	38	31	26	45	36	30	26	23				
	中	0.81	0.8	63	51	43	37	61	50	42	36	57	47	41	35	54	45	39	35	32				
	否	0.77	1.0	69	58	50	44	67	57	49	43	63	54	47	42	59	51	46	41	38				
			1.25	75	65	57	51	73	63	56	50	68	60	54	49	64	57	52	47	44				
下方投影面積	cm ²		1.5	79	70	62	56	77	68	61	55	72	65	59	54	68	62	56	52	48				
等価発光面積	cm ²		2.0	85	77	70	64	82	75	69	63	78	71	66	61	73	68	63	59	55				
取付高さ	器具間隔最大限		2.5	89	81	75	70	横方向 (A)		縦方向 (B)		86	79	74	69	81	76	71	67	77	72	68	65	60
	1.5m	1.94m						1.91m																
2	2.58	2.51	5.0	97	92	88	84	94	90	86	83	89	86	83	80	85	82	80	77	74	72			
2.5	3.23	3.11	7.0	99	96	92	89	97	94	91	88	92	89	87	85	88	86	84	82	77				
3	3.87	3.65	10.0	101	98	96	94	99	96	94	92	94	92	90	89	90	88	87	85	80				

