

屋内照明器具特性

品番 (品名)	XND1535SW	
光源	LED4000_85_1530 ×1	1530.0 lm
管理番号	K0176633(0)DB1	
BZ分類	BZ1	

器具効率	101%	天井	80%				70%				50%				30%				0%		
	上方光束		0%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
下方光束	101%	床	10%				10%				10%				10%				0%		
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.81	0.6	89	84	81	79	89	84	81	79	88	83	81	79	86	83	80	78	78	
	中	0.77	0.8	94	90	87	85	94	90	87	85	92	89	86	84	91	88	86	84	83	
	否	0.68	1.0	97	93	91	88	97	93	90	88	95	92	90	88	94	91	89	87	86	
下方投影面積 等価発光面積	cm ²	1.25	1.00	96	94	92	99	96	93	91	97	95	93	91	96	94	92	90	89		
		1.5	1.01	98	96	94	101	98	95	94	99	97	95	93	97	95	94	92	91		
		2.0	1.03	101	99	97	103	100	98	97	101	99	97	96	99	97	96	95	93		
取付高さ	器具間隔最大限		2.5	1.05	1.03	1.01	99	1.04	1.02	1.00	99	1.02	1.00	99	1.00	99	98	1.00	99	97	95
	横方向 (A)	縦方向 (B)	3.0	1.05	1.04	1.02	1.01	1.04	1.03	1.01	1.00	1.03	1.01	1.00	99	1.01	1.00	99	98	96	
Hm	0.44Hm	0.44Hm	4.0	1.06	1.05	1.04	1.03	1.05	1.04	1.03	1.02	1.03	1.02	1.01	1.00	1.01	1.01	1.00	99	97	
			5.0	1.07	1.06	1.05	1.04	1.06	1.05	1.04	1.03	1.04	1.03	1.02	1.02	1.02	1.01	1.01	1.00	98	
			7.0	1.08	1.07	1.06	1.05	1.07	1.06	1.05	1.04	1.05	1.04	1.03	1.03	1.03	1.02	1.02	1.01	99	
			10.0	1.08	1.08	1.07	1.06	1.07	1.07	1.06	1.05	1.05	1.05	1.04	1.04	1.03	1.03	1.02	1.02	99	

