

# 屋内照明器具特性

品番 (品名)	XND1535SY	
光源	LED2700_85_1380 ×1	1380.0 lm
管理番号	K0176633(0)DB1	
BZ分類	BZ1	

器具効率	101%	天井	80%				70%				50%				30%				0%	
	上方光束		0%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	101%	床	10%				10%				10%				10%				0%	
室指数	照明率 ( X0.01 )																			ZCM
保守率	良	0.81	0.6	89	84	81	79	89	84	81	79	88	83	81	79	86	83	80	78	78
	中	0.77	0.8	94	90	87	85	94	90	87	85	92	89	86	84	91	88	86	84	83
	否	0.68	1.0	97	93	91	88	97	93	90	88	95	92	90	88	94	91	89	87	86
下方投影面積 等価発光面積	cm <sup>2</sup>	1.25	1.00	96	94	92	99	96	93	91	97	95	93	91	96	94	92	90	89	
		1.5	1.01	98	96	94	101	98	95	94	99	97	95	93	97	95	94	92	91	
		2.0	1.03	101	99	97	103	100	98	97	101	99	97	96	99	97	96	95	93	
取付高さ	器具間隔最大限		2.5	1.05	103	101	99	104	102	100	99	102	100	99	98	100	99	98	97	95
	横方向 (A)	縦方向 (B)	3.0	1.05	104	102	101	104	103	101	100	103	101	100	99	101	100	99	98	96
Hm	0.44Hm	0.44Hm	4.0	1.06	105	104	103	105	104	103	102	103	102	101	100	101	101	100	99	97
			5.0	1.07	106	105	104	106	105	104	103	104	103	102	102	102	101	101	100	98
			7.0	1.08	107	106	105	107	106	105	104	105	104	103	103	103	102	102	101	99
			10.0	1.08	108	107	106	107	107	106	105	105	105	104	104	103	103	102	102	99

