

# 屋内照明器具特性

|         |                             |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---------|-----------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | XND2559WN                   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 光源      | LED5000_85_2505 x1 2505.0lm |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0176080(0)DB1              |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ1                         |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

|        |                  |         |               |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |
|--------|------------------|---------|---------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|
| 器具効率   | 100%             | 天井      | 80%           |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |    |    |
|        |                  |         | 反射率           | 壁   | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10 | 0% |
|        |                  |         |               | 床   | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |    | 0% |
| 上方光束   | 0%               | 室指数     | 照明率 ( X0.01 ) |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     | ZCM |    |    |
| 下方光束   | 100%             |         |               |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |
| 保守率    | 良<br>中<br>否      | 0.81    | 0.6           | 72  | 64  | 58  | 54  | 72  | 63  | 58  | 54  | 70  | 63  | 58  | 54  | 68  | 62  | 57  | 54  | 53 |    |
|        |                  | 0.77    | 0.8           | 82  | 74  | 69  | 65  | 81  | 74  | 69  | 65  | 79  | 73  | 68  | 65  | 77  | 72  | 68  | 65  | 63 |    |
|        |                  |         | 1.0           | 87  | 81  | 76  | 73  | 86  | 80  | 76  | 72  | 84  | 79  | 75  | 72  | 82  | 78  | 74  | 72  | 70 |    |
|        |                  | 0.68    | 1.25          | 92  | 86  | 82  | 79  | 91  | 85  | 81  | 78  | 89  | 84  | 81  | 78  | 87  | 83  | 80  | 77  | 76 |    |
| 下方投影面積 | c m <sup>2</sup> | 1.5     | 95            | 90  | 86  | 83  | 94  | 89  | 85  | 82  | 91  | 87  | 84  | 82  | 89  | 86  | 83  | 81  | 79  |    |    |
|        |                  | 2.0     | 98            | 94  | 91  | 88  | 97  | 93  | 90  | 88  | 95  | 92  | 89  | 87  | 93  | 90  | 88  | 86  | 84  |    |    |
| 取付高さ   | 器具間隔最大限          |         | 2.5           | 100 | 97  | 94  | 92  | 99  | 96  | 93  | 91  | 97  | 94  | 92  | 90  | 95  | 93  | 91  | 89  | 87 |    |
|        | 横方向 (A)          | 縦方向 (B) | 3.0           | 102 | 99  | 96  | 94  | 101 | 98  | 96  | 94  | 98  | 96  | 94  | 92  | 96  | 94  | 93  | 91  | 89 |    |
| H m    | 1.10H m          | 1.10H m | 4.0           | 103 | 101 | 99  | 97  | 102 | 100 | 98  | 97  | 100 | 98  | 97  | 95  | 98  | 97  | 95  | 94  | 92 |    |
|        |                  |         | 5.0           | 104 | 103 | 101 | 99  | 103 | 102 | 100 | 99  | 101 | 100 | 98  | 97  | 99  | 98  | 97  | 96  | 93 |    |
|        |                  |         | 7.0           | 106 | 104 | 103 | 102 | 104 | 103 | 102 | 101 | 102 | 101 | 100 | 99  | 100 | 99  | 98  | 98  | 95 |    |
|        |                  |         | 10.0          | 106 | 105 | 105 | 104 | 105 | 104 | 104 | 103 | 103 | 102 | 102 | 101 | 101 | 100 | 100 | 99  | 96 |    |

