

# 屋内照明器具特性

品番 (品名)	XND1566SF	
光源	LED2700_85_1225 ×1 1225.0lm	
管理番号	K0176640(0)DB1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	100%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良 0.81	0.6	79	72	68	64	79	72	67	64	77	71	67	64	76	70	67	64	63	
	中 0.77		0.8	87	81	76	73	86	80	76	73	84	79	76	73	83	78	75	73	71
	否 0.68		1.0	92	86	82	79	91	85	82	79	89	84	81	78	87	83	80	78	77
下方投影面積 等価発光面積	cm <sup>2</sup>	1.25	95	90	87	84	94	90	86	84	92	88	86	83	91	87	85	83	81	
		1.5	98	93	90	87	97	93	90	87	95	91	89	86	93	90	88	86	84	
取付高さ	器具間隔最大限		2.0	100	97	94	92	99	96	94	91	97	95	93	91	95	93	91	88	
	Hm	0.73Hm	0.73Hm	2.5	102	99	97	95	101	98	96	94	99	97	95	93	97	95	94	90
Hm		0.73Hm	0.73Hm	3.0	103	101	99	97	102	100	98	96	100	98	97	95	98	97	95	92
	4.0			105	103	101	100	104	102	100	99	101	100	99	98	99	98	97	96	94
Hm				5.0	106	104	103	101	104	103	102	101	102	101	100	99	100	99	98	95
				7.0	107	105	104	103	105	104	103	102	103	102	101	101	101	100	100	99
Hm				10.0	107	106	106	105	106	105	104	104	103	103	102	102	101	101	100	98

