

# 屋内照明器具特性

品番 (品名)	XND2005SWK	
光源	LED4000_85_1770 ×1	1770.0lm
管理番号	K0176492(0)DB1	
BZ分類	BZ1	

器具効率	101%	天井	80%				70%				50%				30%				0%	
	上方光束		0%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	101%	床	10%				10%				10%				10%				0%	
室指数			照明率 (X0.01)																ZCM	
保守率	良	0.81	0.6	89	83	80	78	88	83	80	78	87	83	80	78	86	82	79	77	76
	中	0.77	0.8	94	89	86	84	93	89	86	84	92	88	85	83	91	87	85	83	82
	否	0.68	1.0	97	93	90	88	96	92	90	87	95	91	89	87	93	91	88	87	86
下方投影面積 等価発光面積	cm <sup>2</sup>	1.25	1.00	96	93	91	99	95	93	91	97	94	92	90	96	93	91	90	88	
		1.5	1.01	98	96	93	100	97	95	93	99	96	94	93	97	95	93	92	90	
		2.0	1.03	101	99	97	102	100	98	96	101	99	97	95	99	97	96	95	93	
取付高さ	器具間隔最大限		2.5	1.05	102	101	99	104	102	100	98	102	100	99	97	100	99	97	96	94
	横方向 (A)	縦方向 (B)	3.0	1.06	104	102	100	104	103	101	100	102	101	100	99	101	99	98	97	95
Hm	0.44Hm	0.44Hm	4.0	1.07	105	104	102	105	104	103	102	103	102	101	100	102	101	100	99	97
			5.0	1.07	106	105	104	106	105	104	103	104	103	102	101	102	101	101	100	98
			7.0	1.08	107	106	105	107	106	105	104	105	104	103	103	103	102	102	101	99
			10.0	1.08	108	107	107	107	107	106	106	105	105	104	104	103	103	102	102	99

