

屋内照明器具特性

品番 (品名)	XND2036WE	
光源	LED3000_85_1525 ×1	1525.0lm
管理番号	K0176630(0)DB1	
BZ分類	BZ1	

器具効率	101%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	101%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良 0.81	0.6	88	82	79	77	87	82	79	77	86	81	79	76	85	81	78	76	75	
	中 0.77		0.8	93	88	85	83	92	88	85	83	91	87	85	83	90	87	84	81	
	否 0.68		1.0	96	92	89	87	96	92	89	87	94	91	88	87	93	90	88	86	85
下方投影面積 等価発光面積	cm ²	1.25	99	95	93	91	98	95	92	90	97	94	92	90	95	93	91	89	88	
		1.5	101	98	95	93	100	97	95	93	98	96	94	92	97	94	93	91	90	
取付高さ	器具間隔最大限		2.5	104	102	100	98	103	101	99	98	101	100	98	97	99	98	97	96	94
	横方向 (A)	縦方向 (B)	3.0	105	103	101	100	104	102	101	99	102	101	99	98	100	99	98	97	95
Hm	0.76Hm	0.76Hm	4.0	106	104	103	102	105	104	102	101	103	102	101	100	101	100	99	98	96
			5.0	107	105	104	103	105	104	103	102	103	103	102	101	101	101	100	99	97
			7.0	107	106	106	105	106	105	104	104	103	103	102	102	101	101	101	101	98
			10.0	108	107	107	106	107	106	106	105	104	104	103	102	102	102	101	101	99

