

屋内照明器具特性	
品番 (品名)	XL X430NEVP
光源	LED3500_85_3040 ×1 3040.0 lm
管理番号	K0135074 (*) DB 1
BZ分類	BZ5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		4 %	室指数	照明率 (X0.01)																			Z	C	M
下方光束		96 %																							
保守率		良 中 否	0.83	0.6	56	44	36	30	54	43	36	30	52	42	35	30	49	40	34	30	27				
			0.81	0.8	66	54	46	41	64	53	46	40	61	51	45	40	58	50	44	39	37				
			0.77	1.0	72	61	54	48	70	60	53	47	67	58	52	47	64	56	51	46	43				
				1.25	78	68	61	55	76	67	60	55	72	65	59	54	69	62	57	53	50				
下方投影面積		cm ²	1.5	82	73	66	60	80	72	65	60	76	69	64	59	73	67	62	58	55					
			2.0	88	80	74	69	86	79	73	68	82	76	71	67	78	73	69	65	62					
等価発光面積		cm ²	2.5	91	85	79	74	89	83	78	73	85	80	76	72	82	77	74	70	67					
			3.0	94	88	83	78	92	86	82	78	88	83	79	76	84	81	77	74	71					
1.5m		1.94 m	2.1 m	4.0	97	92	88	84	95	90	87	83	91	87	84	81	88	85	82	79	76				
2		2.56	2.64	5.0	99	95	91	88	97	93	90	87	93	90	87	85	90	87	85	83	79				
2.5		3.19	3.21	7.0	101	98	95	93	99	96	94	91	96	93	91	89	92	90	88	87	83				
3		3.8	3.79	10.0	103	101	98	96	101	99	97	95	97	96	94	93	94	93	91	90	86				

