

屋内照明器具特性	
品番 (品名)	XND9930SSK
光源	LED5000_80_13800 ×1 13800.0 1 m
管理番号	K0189037(1)D 1
BZ分類	BZ1

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	100%	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否	0.76	0.6	81	75	71	68	81	75	71	68	79	74	70	68	78	73	70	67	66
		0.72	0.8	89	83	79	76	88	82	79	76	86	81	78	76	85	81	78	75	74
		0.64	1.0	93	88	84	81	92	87	84	81	90	86	83	81	89	85	83	80	79
			1.25	96	92	88	86	95	91	88	86	93	90	87	85	92	89	86	85	83
下方投影面積	c m ²	1.5	98	94	91	89	97	94	91	88	95	92	90	88	94	91	89	87	86	
		2.0	101	98	95	93	100	97	94	93	98	95	93	92	96	94	92	91	89	
取付高さ	器具間隔最大限		2.5	102	100	97	96	101	99	97	95	99	97	96	94	97	96	94	93	91
	横方向 (A)	縦方向 (B)	3.0	103	101	99	97	102	100	98	97	100	98	97	96	98	97	96	95	92
H m	1.06 H m	1.06 H m	4.0	105	103	101	100	104	102	100	99	101	100	99	98	99	98	97	96	94
			5.0	105	104	103	101	104	103	102	101	102	101	100	99	100	99	98	98	95
			7.0	106	105	104	103	105	104	103	102	103	102	101	101	101	100	100	99	97
			10.0	107	106	105	105	106	105	104	104	104	103	102	102	101	101	101	100	97

