

屋内照明器具特性	
品番 (品名)	XL X4 6 0 S DNT
光源	LED5000_85_6180 ×1 6180.0 lm
管理番号	K0132112 (*) DB 1
B Z 分類	BZ5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						室指数	照明率 (X0.01)															
保守率		良 中 否	0.81	0.6	56	43	35	30	54	42	35	29	52	41	34	29	50	40	34	29	27	
			0.77	0.8	66	54	46	40	64	53	45	40	61	51	45	39	59	50	44	39	37	
			0.68	1.0	72	61	53	47	70	60	53	47	67	58	52	46	65	57	51	46	44	
				1.25	78	68	60	54	76	67	60	54	73	65	59	54	70	63	58	53	51	
下方投影面積		cm ²		1.5	82	73	66	60	81	72	65	60	77	70	64	59	74	68	63	59	56	
				2.0	88	80	74	69	86	79	73	68	83	77	72	67	80	75	71	67	64	
等価発光面積		cm ²		2.5	92	85	79	75	90	84	79	74	87	82	77	73	84	79	76	72	69	
				3.0	94	88	83	79	93	87	83	78	90	85	81	77	87	83	79	76	73	
1.5m		1.98 m	2.17 m		4.0	98	93	89	85	96	92	88	84	93	89	86	83	90	87	84	79	
2		2.62	2.74		5.0	100	96	92	89	98	95	91	88	95	92	89	87	92	90	88	85	83
2.5		3.25	3.32		7.0	102	99	96	94	101	98	95	93	98	95	93	91	95	93	91	90	87
3		3.88	3.92		10.0	104	102	100	98	102	100	99	97	100	98	97	95	97	96	95	93	90

