

屋内照明器具特性	
品番 (品名)	XL X440 ME WP
光源	LED4000_85_3470 ×1 3470.0 lm
管理番号	K0129807 (7) DB 1
BZ分類	BZ5/0.7/BZ4

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 8 1	0 . 6	5 8	4 6	3 9	3 3	5 7	4 6	3 8	3 3	5 4	4 4	3 8	3 3	5 2	4 3	3 7	3 3	3 1
			0 . 7 7	0 . 8	6 8	5 7	5 0	4 4	6 7	5 7	4 9	4 4	6 4	5 5	4 9	4 4	6 2	5 4	4 8	4 4	4 2
			0 . 6 8	1 . 0	7 5	6 5	5 8	5 2	7 4	6 4	5 7	5 2	7 1	6 3	5 6	5 2	6 8	6 1	5 6	5 1	4 9
				1 . 2 5	8 1	7 2	6 5	6 0	8 0	7 1	6 5	6 0	7 7	6 9	6 4	5 9	7 4	6 8	6 3	5 9	5 6
下方投影面積		c m ²	1 . 5	8 5	7 7	7 1	6 5	8 4	7 6	7 0	6 5	8 1	7 4	6 9	6 4	7 8	7 2	6 8	6 4	6 2	
			等価発光面積	c m ²	2 . 0	9 1	8 4	7 8	7 4	8 9	8 3	7 8	7 3	8 6	8 1	7 6	7 2	8 3	7 9	7 5	7 2
取付 高さ	器具間隔最大限		2 . 5	9 4	8 8	8 3	7 9	9 2	8 7	8 3	7 9	9 0	8 5	8 1	7 8	8 7	8 3	8 0	7 7	7 4	
	横方向 (A)	縦方向 (B)	3 . 0	9 6	9 1	8 7	8 3	9 5	9 0	8 6	8 3	9 2	8 8	8 5	8 1	8 9	8 6	8 3	8 0	7 8	
1 . 5 m	2 m	2 . 2 1 m	4 . 0	9 9	9 5	9 2	8 9	9 8	9 4	9 1	8 8	9 5	9 2	8 9	8 7	9 2	9 0	8 7	8 5	8 3	
2	2 . 6 5	2 . 7 9	5 . 0	1 0 1	9 8	9 5	9 2	1 0 0	9 7	9 4	9 1	9 7	9 4	9 2	9 0	9 4	9 2	9 0	8 8	8 6	
2 . 5	3 . 3	3 . 4	7 . 0	1 0 3	1 0 1	9 8	9 6	1 0 2	9 9	9 7	9 5	9 9	9 7	9 5	9 4	9 7	9 5	9 4	9 2	8 9	
3	3 . 9 5	4 . 0 2	1 0 . 0	1 0 5	1 0 3	1 0 1	1 0 0	1 0 3	1 0 2	1 0 0	9 9	1 0 1	9 9	9 8	9 7	9 8	9 7	9 6	9 5	9 2	

