

屋内照明器具特性

品番 (品名)	XND2518WWK	
光源	LED4000_85_2500 ×1	2500.0lm
管理番号	K0176485(0)DB1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	100%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良 0.81	0.6	77	70	65	61	76	69	64	61	75	68	64	61	73	68	64	61	60	
	中 0.77		0.8	85	78	74	70	84	78	74	70	82	77	73	70	81	76	73	70	68
	否 0.68		1.0	90	84	80	76	89	83	79	76	87	82	79	76	85	81	78	76	74
下方投影面積	cm ²	1.25	94	89	85	82	93	88	84	82	91	87	84	81	89	86	83	80	79	
		1.5	96	92	88	85	95	91	88	85	93	90	87	85	91	88	86	84	82	
等価発光面積	cm ²	2.0	100	96	93	90	99	95	92	90	96	94	91	89	95	92	90	88	86	
		2.5	102	98	96	94	100	98	95	93	98	96	94	92	96	94	93	91	89	
取付高さ	器具間隔最大限		3.0	103	100	98	96	102	99	97	95	99	97	96	94	97	96	94	93	91
	横方向 (A)	縦方向 (B)	4.0	104	102	100	99	103	101	100	98	101	99	98	97	99	98	96	95	93
Hm	0.74Hm	0.74Hm	5.0	105	104	102	101	104	103	101	100	102	101	99	98	100	99	98	97	94
			7.0	106	105	104	103	105	104	103	102	103	102	101	100	101	100	99	99	96
			10.0	107	106	105	104	106	105	104	104	104	103	102	102	101	101	100	100	97

