

屋内照明器具特性

| | | |
|---------|--------------------|----------|
| 品番 (品名) | XND3538WN | |
| 光源 | LED5000_80_4140 ×1 | 4140.0lm |
| 管理番号 | K0179574(0)DB1 | |
| BZ分類 | BZ1 | |

| | | | | | | | | | | | | | | | | | | | | |
|--------|---------|-----------------|-------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|
| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | 上方光束 | | 0% | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% |
| 下方光束 | 100% | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% | |
| 室指数 | | | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 | 0.76 | 0.6 | 74 | 66 | 60 | 56 | 73 | 65 | 60 | 56 | 71 | 64 | 60 | 56 | 70 | 64 | 59 | 56 | 55 |
| | 中 | 0.72 | 0.8 | 82 | 75 | 70 | 66 | 81 | 74 | 70 | 66 | 79 | 73 | 69 | 66 | 78 | 72 | 69 | 66 | 64 |
| | 否 | 0.64 | 1.0 | 87 | 81 | 76 | 73 | 86 | 80 | 76 | 72 | 84 | 79 | 75 | 72 | 82 | 78 | 74 | 72 | 70 |
| 下方投影面積 | 等価発光面積 | cm ² | 1.25 | 92 | 86 | 82 | 78 | 91 | 85 | 81 | 78 | 88 | 84 | 80 | 77 | 87 | 83 | 80 | 77 | 75 |
| | | | 1.5 | 95 | 89 | 85 | 82 | 93 | 89 | 85 | 82 | 91 | 87 | 84 | 81 | 89 | 86 | 83 | 81 | 79 |
| 取付高さ | 器具間隔最大限 | | 2.0 | 98 | 94 | 91 | 88 | 97 | 93 | 90 | 87 | 95 | 91 | 89 | 86 | 93 | 90 | 88 | 86 | 84 |
| | 横方向 (A) | 縦方向 (B) | 2.5 | 100 | 97 | 94 | 91 | 99 | 96 | 93 | 91 | 97 | 94 | 92 | 90 | 95 | 92 | 90 | 89 | 87 |
| Hm | 0.73Hm | 0.73Hm | 3.0 | 102 | 99 | 96 | 94 | 100 | 98 | 95 | 93 | 98 | 96 | 94 | 92 | 96 | 94 | 92 | 91 | 89 |
| | | | 4.0 | 103 | 101 | 99 | 97 | 102 | 100 | 98 | 96 | 100 | 98 | 96 | 95 | 98 | 96 | 95 | 94 | 91 |
| | | | 5.0 | 104 | 102 | 101 | 99 | 103 | 101 | 100 | 98 | 101 | 99 | 98 | 97 | 99 | 98 | 96 | 95 | 93 |
| | | | 7.0 | 106 | 104 | 103 | 102 | 104 | 103 | 102 | 101 | 102 | 101 | 100 | 99 | 100 | 99 | 98 | 97 | 95 |
| | | | 10.0 | 106 | 105 | 104 | 104 | 105 | 104 | 103 | 103 | 103 | 102 | 101 | 101 | 101 | 100 | 100 | 99 | 96 |

