

# 屋内照明器具特性

品番 (品名)	XND5 5 3 7 WV															
光源	LED3500_80_5075 x1 5075.0 lm															
管理番号	K0179592 (1) DB 1															
BZ分類	BZ1/3.5/BZ2/8.5/BZ1															

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%	反射率	10%				10%				10%				10%				0%	
下方光束	100%		床	10%				10%				10%				10%				0%
		室指数	照明率 ( X0.01 ) ZCM																	
保守率	良 中 否	0.76	0.6	75	67	61	58	74	66	61	58	72	65	61	58	71	65	60	57	56
		0.72	0.8	83	75	70	67	82	75	70	67	80	74	69	66	78	73	69	66	65
			1.0	88	81	76	73	86	80	76	72	84	79	75	72	83	78	75	72	70
		0.64	1.25	92	86	81	78	90	85	81	78	88	84	80	77	86	82	79	77	75
下方投影面積	c m <sup>2</sup>	1.5	94	89	85	82	93	88	84	81	91	87	83	81	89	85	82	80	78	
		2.0	98	93	90	87	96	93	89	87	94	91	88	86	92	89	87	85	83	
取付高さ	器具間隔最大限		2.5	100	96	93	90	99	95	92	90	96	93	91	89	94	92	90	88	
	横方向 (A)	縦方向 (B)	3.0	101	98	95	93	100	97	95	92	98	95	93	91	96	94	92	90	
H m	1.20 H m	1.20 H m	4.0	103	101	98	96	102	100	97	96	99	98	96	94	97	96	94	93	
			5.0	104	102	100	98	103	101	99	98	101	99	98	96	98	97	96	95	
			7.0	105	104	102	101	104	103	101	100	102	101	100	99	100	99	98	97	
			10.0	106	105	104	103	105	104	103	102	103	102	101	100	101	100	99	99	

