

# 屋内照明器具特性

品番 (品名)	XND5566SA	
光源	LED5000_80_4590 ×1	4590.0 lm
管理番号	K0179571(0)DB1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	壁	照明率 ( X0.01 )																ZCM	
下方光束	100%	床	照明率 ( X0.01 )																ZCM	
保守率	良 中 否	0.76 0.72 0.64	室指数																	
						0.6	79	71	67	63	78	71	66	63	76	70	66	63	75	69
			0.8	86	80	76	72	85	79	75	72	84	79	75	72	82	78	74	72	70
			1.0	91	85	81	78	90	85	81	78	88	84	80	78	86	83	80	77	76
			1.25	95	90	86	83	94	89	86	83	92	88	85	82	90	87	84	82	80
			1.5	97	93	89	87	96	92	89	86	94	91	88	86	92	89	87	85	83
			2.0	100	97	94	91	99	96	93	91	97	94	92	90	95	93	91	89	87
			2.5	102	99	96	94	101	98	96	94	99	96	94	93	97	95	93	92	90
			3.0	103	100	98	96	102	100	98	96	100	98	96	95	98	96	95	93	91
			4.0	104	102	101	99	103	101	100	98	101	100	98	97	99	98	97	96	93
			5.0	105	104	102	101	104	103	101	100	102	101	100	99	100	99	98	97	95
			7.0	106	105	104	103	105	104	103	102	103	102	101	100	101	100	99	99	96
			10.0	107	106	105	104	106	105	104	104	103	103	102	102	101	101	100	100	97

