

屋内照明器具特性

品番 (品名)	XNN1061PA				
光源	LED5000_85_670	x1	670.0	lm	
管理番号	K0190269(0)DB1				
BZ分類	BZ4				

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	100%	床		10%				10%				10%				10%				0%
室指数			照明率 (X0.01)																ZCM	
保守率	良	0.83	0.6	60	49	42	37	59	48	41	37	57	47	41	36	55	46	41	36	34
	中	0.81	0.8	71	60	53	48	69	59	52	47	67	58	52	47	64	57	51	47	45
	否	0.77	1.0	77	67	60	55	76	67	60	55	73	65	59	55	70	64	59	54	52
			1.25	83	74	68	63	81	73	67	62	79	72	66	62	76	70	65	61	59
下方投影面積		cm ²	1.5	87	79	73	68	85	78	72	68	82	76	71	67	80	74	70	66	64
等価発光面積		cm ²	2.0	92	85	80	76	90	84	79	75	87	82	78	74	85	81	77	74	71
取付高さ	器具間隔最大限		2.5	95	89	85	81	93	88	84	80	91	86	83	79	88	84	81	78	76
	横方向 (A)	縦方向 (B)	3.0	97	92	88	85	96	91	87	84	93	89	86	83	90	87	84	82	79
Hm	1.19Hm	1.19Hm	4.0	100	96	93	90	98	95	92	89	96	93	90	88	93	91	89	87	84
			5.0	102	98	96	93	100	97	95	92	98	95	93	91	95	93	91	89	87
			7.0	103	101	99	97	102	100	98	96	100	98	96	95	97	96	94	93	90
			10.0	105	103	102	100	104	102	101	99	101	100	99	97	99	98	97	96	93

