

屋内照明器具特性	
品番 (品名)	XND7539SV
光源	LED3500_80_6910 x1 6910.0lm
管理番号	K0179814(0)DB1
BZ分類	BZ1

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	100%	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否	0.76	0.6	77	70	65	62	76	69	65	62	75	69	64	61	73	68	64	61	60
		0.72	0.8	86	79	75	71	85	79	74	71	83	78	74	71	81	77	73	71	69
		0.64	1.0	91	85	81	78	90	84	80	77	88	83	80	77	86	82	79	77	75
			1.25	94	89	86	83	93	89	85	83	91	88	85	82	90	86	84	82	80
下方投影面積		c m ²	1.5	97	92	89	86	96	92	89	86	94	90	88	85	92	89	87	85	83
等価発光面積		c m ²	2.0	100	96	93	91	99	95	93	91	97	94	92	90	95	93	91	89	87
取付高さ	器具間隔最大限		2.5	102	99	96	94	100	98	96	94	98	96	94	93	96	95	93	92	90
	横方向 (A)	縦方向 (B)	3.0	103	100	98	96	102	99	97	96	99	98	96	94	98	96	95	93	91
Hm	1.13Hm	1.13Hm	4.0	104	102	100	99	103	101	100	98	101	99	98	97	99	98	97	96	93
			5.0	105	103	102	101	104	102	101	100	102	101	99	98	100	99	98	97	95
			7.0	106	105	104	103	105	104	103	102	103	102	101	100	101	100	99	99	96
			10.0	107	106	105	104	106	105	104	103	103	103	102	102	101	101	100	100	97

