

屋内照明器具特性

品番 (品名)	XND7566WW	
光源	LED4000_80_7755 x1	7755.0lm
管理番号	K0179582(1)DB1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	壁	照明率 (X0.01)																ZCM	
下方光束	100%	床	照明率 (X0.01)																ZCM	
保守率	良 中 否	0.76 0.72 0.64	室指数																	
						0.6	77	69	64	61	76	69	64	61	74	68	64	61	73	67
			0.8	85	78	73	70	84	77	73	69	82	76	72	69	80	75	72	69	68
			1.0	89	83	79	75	88	82	78	75	86	81	78	75	84	80	77	74	73
			1.25	93	88	84	80	92	87	83	80	90	86	82	80	88	84	82	79	78
			1.5	96	91	87	84	94	90	87	84	92	89	86	83	90	87	85	82	81
			2.0	99	95	92	89	98	94	91	89	96	92	90	88	94	91	89	87	85
			2.5	101	97	95	92	100	97	94	92	97	95	93	91	95	93	91	90	88
			3.0	102	99	97	95	101	98	96	94	99	96	95	93	97	95	93	92	90
			4.0	104	101	99	98	103	100	99	97	100	99	97	96	98	97	95	94	92
			5.0	105	103	101	100	103	102	100	99	101	100	99	97	99	98	97	96	93
			7.0	106	104	103	102	105	103	102	101	102	101	100	99	100	99	99	98	95
			10.0	107	106	105	104	105	104	103	103	102	102	101	101	100	100	100	99	97

