

屋内照明器具特性

品番 (品名)	XND7567SE									
光源	LED3000_80_6215 x1 6215.0 lm									
管理番号	K0179587(1)DB1									
BZ分類	BZ1									

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%																			
下方光束	100%																			
室指数			照明率 (X0.01)																ZCM	
保守率	良	0.76	0.6	81	74	70	67	80	74	70	67	79	73	69	67	77	72	69	66	65
	中	0.72	0.8	88	82	78	75	87	82	78	75	86	81	77	75	84	80	77	75	73
	否	0.64	1.0	92	87	84	81	92	87	83	81	90	86	83	80	88	85	82	80	79
			1.25	96	91	88	85	95	91	88	85	93	90	87	85	91	88	86	84	83
下方投影面積		cm ²	1.5	98	94	91	88	97	93	90	88	95	92	90	88	93	91	89	87	85
等価発光面積		cm ²	2.0	101	97	95	93	100	97	94	92	98	95	93	91	96	94	92	91	89
取付高さ	器具間隔最大限		2.5	102	100	97	95	101	99	97	95	99	97	95	94	97	96	94	93	91
	横方向 (A)	縦方向 (B)	3.0	103	101	99	97	102	100	98	97	100	98	97	95	98	97	96	94	92
Hm	0.95Hm	0.95Hm	4.0	105	103	101	100	103	102	100	99	101	100	99	98	99	98	97	96	94
			5.0	105	104	103	101	104	103	102	101	102	101	100	99	100	99	98	98	95
			7.0	106	105	104	103	105	104	103	102	103	102	101	101	101	100	100	99	96
			10.0	107	106	105	105	106	105	104	104	104	103	102	102	101	101	101	100	97

