

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | XLY090EL                     |
| 光源       | LED3000_85_1090 ×1 1090.0 lm |
| 管理番号     | K0155409 ( 0 ) DB 1          |
| BZ分類     | BZ5                          |

| 器具効率         |                     | 100 %           | 反射率  | 天井                | 80 % |     |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |  |
|--------------|---------------------|-----------------|------|-------------------|------|-----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|--|
|              |                     |                 |      | 壁                 | 70   | 50  | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |  |
|              |                     |                 |      | 床                 | 10 % |     |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |  |
| 上方光束<br>下方光束 |                     | 6 %<br>94 %     | 室指数  | 照明率 ( X0.01 ) ZCM |      |     |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |  |
| 保守率          |                     | 良<br>中<br>否     | 0.83 | 0.6               | 55   | 42  | 34 | 29 | 53   | 41 | 34 | 28 | 50   | 40 | 33 | 28 | 47   | 38 | 32 | 28 | 25  |  |
|              |                     |                 | 0.81 | 0.8               | 64   | 52  | 44 | 38 | 62   | 51 | 44 | 38 | 59   | 49 | 43 | 37 | 56   | 48 | 41 | 37 | 34  |  |
|              |                     |                 | 0.77 | 1.0               | 71   | 60  | 52 | 46 | 69   | 58 | 51 | 45 | 65   | 56 | 49 | 44 | 62   | 54 | 48 | 43 | 41  |  |
|              |                     |                 |      | 1.25              | 77   | 66  | 59 | 53 | 75   | 65 | 58 | 52 | 71   | 62 | 56 | 51 | 67   | 60 | 55 | 50 | 47  |  |
| 下方投影面積       |                     | cm <sup>2</sup> |      | 1.5               | 81   | 71  | 64 | 58 | 79   | 70 | 63 | 58 | 75   | 67 | 61 | 56 | 71   | 65 | 59 | 55 | 52  |  |
| 等価発光面積       |                     | cm <sup>2</sup> |      | 2.0               | 86   | 78  | 72 | 66 | 84   | 77 | 71 | 66 | 80   | 74 | 69 | 64 | 76   | 71 | 67 | 63 | 59  |  |
| 取付<br>高さ     | 器具間隔最大限             |                 |      | 2.5               | 90   | 83  | 77 | 72 | 88   | 81 | 76 | 71 | 84   | 78 | 74 | 69 | 80   | 75 | 71 | 68 | 64  |  |
|              | 横方向 ( A ) 縦方向 ( B ) |                 |      | 3.0               | 92   | 86  | 81 | 76 | 90   | 85 | 80 | 75 | 86   | 81 | 77 | 74 | 82   | 78 | 75 | 72 | 68  |  |
| 1.5m         | 1.96 m              | 2 m             |      | 4.0               | 96   | 91  | 86 | 82 | 94   | 89 | 85 | 81 | 90   | 86 | 82 | 79 | 86   | 83 | 80 | 77 | 73  |  |
| 2            | 2.6                 | 2.58            |      | 5.0               | 98   | 94  | 90 | 86 | 96   | 92 | 88 | 85 | 92   | 88 | 85 | 83 | 88   | 85 | 83 | 80 | 76  |  |
| 2.5          | 3.24                | 3.18            |      | 7.0               | 100  | 97  | 94 | 91 | 98   | 95 | 92 | 90 | 94   | 92 | 89 | 87 | 91   | 89 | 87 | 85 | 81  |  |
| 3            | 3.87                | 3.78            |      | 10.0              | 102  | 100 | 97 | 95 | 100  | 98 | 96 | 94 | 96   | 94 | 93 | 91 | 93   | 91 | 90 | 88 | 84  |  |

