

# 屋内照明器具特性

|         |                     |            |
|---------|---------------------|------------|
| 品番 (品名) | XND9998SNZ          |            |
| 光源      | LED5000_80_16095 x1 | 16095.0 1m |
| 管理番号    | K0188264(0)DB1      |            |
| BZ分類    | BZ1                 |            |

|        |               |                 |      |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |     |
|--------|---------------|-----------------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|-----|
| 器具効率   | 100%          | 天井              | 80%  |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0% |    |     |
|        | 上方光束<br>0%    |                 | 壁    | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10 | 0% |     |
| 下方光束   | 100%          | 床               |      | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |    | 0% |     |
| 室指数    | 照明率 ( X0.01 ) |                 |      |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    | ZCM |
| 保守率    | 良             | 0.76            | 0.6  | 74  | 65  | 60  | 56  | 73  | 65  | 60  | 56  | 71  | 64  | 59  | 56  | 70  | 63  | 59  | 56 | 55 |     |
|        | 中             | 0.72            | 0.8  | 82  | 75  | 70  | 66  | 81  | 74  | 70  | 66  | 80  | 73  | 69  | 66  | 78  | 72  | 69  | 66 | 64 |     |
|        | 否             | 0.64            | 1.0  | 88  | 81  | 76  | 73  | 87  | 80  | 76  | 73  | 85  | 79  | 75  | 72  | 83  | 78  | 75  | 72 | 70 |     |
| 下方投影面積 | 等価発光面積        | cm <sup>2</sup> | 1.25 | 92  | 86  | 82  | 79  | 91  | 86  | 82  | 78  | 89  | 84  | 81  | 78  | 87  | 83  | 80  | 77 | 76 |     |
|        |               |                 | 1.5  | 95  | 90  | 86  | 83  | 94  | 89  | 85  | 82  | 92  | 88  | 84  | 82  | 90  | 86  | 83  | 81 | 79 |     |
| 取付高さ   | 器具間隔最大限       |                 | 2.0  | 98  | 94  | 91  | 88  | 97  | 94  | 90  | 88  | 95  | 92  | 89  | 87  | 93  | 90  | 88  | 86 | 84 |     |
|        | 横方向 (A)       | 縦方向 (B)         | 2.5  | 101 | 97  | 94  | 92  | 99  | 96  | 94  | 91  | 97  | 95  | 92  | 90  | 95  | 93  | 91  | 89 | 87 |     |
| Hm     | 0.71Hm        | 0.71Hm          | 3.0  | 102 | 99  | 97  | 94  | 101 | 98  | 96  | 94  | 99  | 96  | 94  | 93  | 96  | 95  | 93  | 91 | 89 |     |
|        |               |                 | 4.0  | 104 | 101 | 99  | 98  | 103 | 100 | 99  | 97  | 100 | 99  | 97  | 95  | 98  | 97  | 95  | 94 | 92 |     |
|        |               |                 | 5.0  | 105 | 103 | 101 | 100 | 104 | 102 | 100 | 99  | 101 | 100 | 99  | 97  | 99  | 98  | 97  | 96 | 93 |     |
|        |               |                 | 7.0  | 106 | 104 | 103 | 102 | 105 | 103 | 102 | 101 | 102 | 101 | 100 | 99  | 100 | 99  | 99  | 98 | 95 |     |
|        |               |                 | 10.0 | 107 | 106 | 105 | 104 | 106 | 105 | 104 | 103 | 103 | 103 | 102 | 101 | 101 | 100 | 100 | 99 | 97 |     |

