

屋内照明器具特性	
品番 (品名)	XL X450NEVP
光源	LED3500_85_4830 ×1 4830.0 lm
管理番号	K0135074 (*) DB 1
BZ分類	BZ5

器具効率		100 %		反射率	天井	80 %				70 %				50 %				30 %				0 %
					壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
					床	10 %				10 %				10 %				10 %				0 %
					室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.83	0.6	56	44	36	30	54	43	36	30	52	42	35	30	49	40	34	30	27	
			0.81	0.8	66	54	46	41	64	53	46	40	61	51	45	40	58	50	44	39	37	
			0.77	1.0	72	61	54	48	70	60	53	47	67	58	52	47	64	56	51	46	43	
			1.25	78	68	61	55	76	67	60	55	72	65	59	54	69	62	57	53	50		
下方投影面積		cm ²	1.5	82	73	66	60	80	72	65	60	76	69	64	59	73	67	62	58	55		
			等価発光面積	cm ²	2.0	88	80	74	69	86	79	73	68	82	76	71	67	78	73	69	65	62
取付高さ	器具間隔最大限			2.5	91	85	79	74	89	83	78	73	85	80	76	72	82	77	74	70	67	
	横方向 (A)		縦方向 (B)	3.0	94	88	83	78	92	86	82	78	88	83	79	76	84	81	77	74	71	
1.5m	1.94m	2.1m	4.0	97	92	88	84	95	90	87	83	91	87	84	81	88	85	82	79	76		
2	2.56	2.64	5.0	99	95	91	88	97	93	90	87	93	90	87	85	90	87	85	83	79		
2.5	3.19	3.21	7.0	101	98	95	93	99	96	94	91	96	93	91	89	92	90	88	87	83		
3	3.8	3.79	10.0	103	101	98	96	101	99	97	95	97	96	94	93	94	93	91	90	86		

