

屋内照明器具特性	
品番 (品名)	XLX450NENP+FSK41020
光源	LED5000_85_4040 ×1 4040.0 lm
管理番号	K0139114 (4) DR1
BZ分類	BZ6

器具効率		100 % 上方光束 15 % 下方光束 85 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.81	0.6	52	39	31	25	50	38	30	25	46	36	29	24	42	33	27	23	20
			0.77	0.8	61	49	40	34	58	47	39	33	54	44	37	32	50	41	35	31	27
			0.68	1.0	67	55	47	41	64	54	46	40	59	50	44	38	55	47	41	37	33
				1.25	73	62	54	48	70	60	52	47	65	56	50	45	60	53	47	43	38
下方投影面積 等価発光面積		cm ²		1.5	77	67	59	53	74	65	57	52	68	61	54	49	63	57	52	47	42
				2.0	83	74	67	61	79	72	65	60	74	67	62	57	68	63	58	54	49
取付 高さ	器具間隔最大限			2.5	86	79	72	67	83	76	70	65	77	71	66	62	72	67	63	59	53
	横方向 (A) 縦方向 (B)			3.0	89	82	76	71	86	79	74	69	80	75	70	66	74	70	66	63	57
1.5m	1.67 m	2.16 m		4.0	92	87	82	77	89	84	79	75	83	79	75	72	78	74	71	68	62
2	2.21	2.72		5.0	94	90	85	81	91	87	83	79	85	82	79	75	80	77	74	72	65
2.5	2.74	3.3		7.0	97	93	90	87	94	91	87	84	88	85	83	80	83	80	78	76	70
3	3.28	3.9		10.0	99	96	94	91	96	94	91	89	90	88	86	84	85	83	82	80	73

