

屋内照明器具特性

品番 (品名)	XND2005SVZ	
光源	LED3500_85_1740 ×1	1740.0lm
管理番号	K0176492(0)DB1	
BZ分類	BZ1	

器具効率	101%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	101%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良 0.81	0.6	89	83	80	78	88	83	80	78	87	83	80	78	86	82	79	77	76	
	中 0.77		0.8	94	89	86	84	93	89	86	84	92	88	85	83	91	87	85	83	82
	否 0.68		1.0	97	93	90	88	96	92	90	87	95	91	89	87	93	91	88	87	86
下方投影面積 等価発光面積	cm ²	1.25	100	96	93	91	99	95	93	91	97	94	92	90	96	93	91	90	88	
		1.5	101	98	96	93	100	97	95	93	99	96	94	93	97	95	93	92	90	
		2.0	103	101	99	97	102	100	98	96	101	99	97	95	99	97	96	95	93	
取付高さ	器具間隔最大限		2.5	105	102	101	99	104	102	100	98	102	100	99	97	100	99	97	96	94
	横方向 (A)	縦方向 (B)	3.0	106	104	102	100	104	103	101	100	102	101	100	99	101	99	98	97	95
Hm	0.44Hm	0.44Hm	4.0	107	105	104	102	105	104	103	102	103	102	101	100	102	101	100	99	97
			5.0	107	106	105	104	106	105	104	103	104	103	102	101	102	101	101	100	98
			7.0	108	107	106	105	107	106	105	104	105	104	103	103	103	102	102	101	99
			10.0	108	108	107	107	107	107	106	106	105	105	104	104	103	103	102	102	99

