

| 屋内照明器具特性 |                             |
|----------|-----------------------------|
| 品番 (品名)  | XND0 6 7 9 WV K             |
| 光源       | LED3500_85_600 x1 600.0 l m |
| 管理番号     | K0176095 ( 0 ) DB 1         |
| B Z 分類   | BZ1                         |

| 器具効率             |                     | 100 %                              | 反射率  | 天井                 | 80 % |     |     |     | 70 % |     |     |     | 50 % |     |     |     | 30 % |     |    |    | 0 % |  |
|------------------|---------------------|------------------------------------|------|--------------------|------|-----|-----|-----|------|-----|-----|-----|------|-----|-----|-----|------|-----|----|----|-----|--|
|                  |                     |                                    |      | 壁                  | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30 | 10 | 0 % |  |
|                  |                     |                                    |      | 床                  | 10 % |     |     |     | 10 % |     |     |     | 10 % |     |     |     | 10 % |     |    |    | 0 % |  |
| 上方光束<br>下方光束     |                     | 100 %                              | 室指数  | 照明率 ( X0.01 ) Z CM |      |     |     |     |      |     |     |     |      |     |     |     |      |     |    |    |     |  |
| 保守率              |                     | 良<br>中<br>否                        | 0.6  | 72                 | 63   | 57  | 54  | 71  | 63   | 57  | 53  | 69  | 62   | 57  | 53  | 67  | 61   | 57  | 53 | 52 |     |  |
|                  |                     |                                    | 0.8  | 81                 | 73   | 68  | 64  | 80  | 73   | 68  | 64  | 78  | 72   | 67  | 64  | 76  | 71   | 67  | 64 | 62 |     |  |
|                  |                     |                                    | 1.0  | 87                 | 80   | 75  | 72  | 86  | 79   | 75  | 71  | 84  | 78   | 74  | 71  | 82  | 77   | 74  | 71 | 69 |     |  |
|                  |                     |                                    | 0.68 | 1.25               | 91   | 86  | 81  | 78  | 90   | 85  | 81  | 77  | 88   | 83  | 80  | 77  | 86   | 82  | 79 | 76 | 75  |  |
| 下方投影面積<br>等価発光面積 |                     | cm <sup>2</sup><br>cm <sup>2</sup> | 1.5  | 94                 | 89   | 85  | 82  | 93  | 88   | 85  | 82  | 91  | 87   | 84  | 81  | 89  | 85   | 83  | 80 | 79 |     |  |
|                  |                     |                                    | 2.0  | 98                 | 94   | 90  | 88  | 97  | 93   | 90  | 87  | 95  | 91   | 89  | 86  | 92  | 90   | 87  | 85 | 84 |     |  |
| 取付<br>高さ         | 器具間隔最大限             |                                    | 2.5  | 100                | 97   | 94  | 91  | 99  | 96   | 93  | 91  | 97  | 94   | 92  | 90  | 95  | 92   | 90  | 89 | 87 |     |  |
|                  | 横方向 ( A ) 縦方向 ( B ) |                                    | 3.0  | 101                | 99   | 96  | 94  | 100 | 98   | 95  | 93  | 98  | 96   | 94  | 92  | 96  | 94   | 92  | 91 | 89 |     |  |
| H m              | 1.13 H m            | 1.13 H m                           | 4.0  | 103                | 101  | 99  | 97  | 102 | 100  | 98  | 96  | 100 | 98   | 96  | 95  | 98  | 96   | 95  | 94 | 91 |     |  |
|                  |                     |                                    | 5.0  | 104                | 102  | 101 | 99  | 103 | 101  | 100 | 98  | 101 | 99   | 98  | 97  | 99  | 98   | 96  | 95 | 93 |     |  |
|                  |                     |                                    | 7.0  | 105                | 104  | 103 | 102 | 104 | 103  | 102 | 101 | 102 | 101  | 100 | 99  | 100 | 99   | 98  | 97 | 95 |     |  |
|                  |                     |                                    | 10.0 | 106                | 105  | 104 | 103 | 105 | 104  | 103 | 103 | 103 | 102  | 101 | 101 | 101 | 100  | 100 | 99 | 96 |     |  |

