

屋内照明器具特性	
品番 (品名)	XND2009BWK
光源	LED4000_85_1955 ×1 1955.0lm
管理番号	K0176488 (0) DB1
BZ分類	BZ1

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		1 0 0 %	室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 8 1	0 . 6	7 5	6 7	6 2	5 8	7 4	6 6	6 2	5 8	7 2	6 6	6 1	5 8	7 1	6 5	6 1	5 8	5 6	
			0 . 7 7	0 . 8	8 4	7 7	7 2	6 8	8 3	7 6	7 2	6 8	8 1	7 5	7 1	6 8	7 9	7 4	7 1	6 8	6 6	
			1 . 0	8 9	8 3	7 9	7 5	8 8	8 2	7 8	7 5	8 6	8 1	7 8	7 5	8 4	8 0	7 7	7 4	7 3		
			0 . 6 8	1 . 2 5	9 3	8 8	8 4	8 1	9 2	8 7	8 4	8 1	9 0	8 6	8 3	8 0	8 8	8 5	8 2	8 0	7 8	
下方投影面積		c m ²	1 . 5	9 6	9 1	8 7	8 5	9 5	9 0	8 7	8 4	9 3	8 9	8 6	8 4	9 1	8 8	8 5	8 3	8 1		
等価発光面積			c m ²	2 . 0	9 9	9 5	9 2	9 0	9 8	9 5	9 2	8 9	9 6	9 3	9 1	8 8	9 4	9 1	8 9	8 8	8 6	
取付高さ				器具間隔最大限		2 . 5	1 0 1	9 8	9 5	9 3	1 0 0	9 7	9 5	9 2	9 8	9 5	9 3	9 1	9 6	9 4	9 2	9 0
H m		1 . 1 0 H m	縦方向 (B)	3 . 0	1 0 2	1 0 0	9 7	9 5	1 0 1	9 9	9 7	9 5	9 9	9 7	9 5	9 4	9 7	9 5	9 4	9 2	9 0	
H m		1 . 1 0 H m		4 . 0	1 0 4	1 0 2	1 0 0	9 8	1 0 3	1 0 1	9 9	9 8	1 0 1	9 9	9 8	9 6	9 8	9 7	9 6	9 5	9 3	
				5 . 0	1 0 5	1 0 3	1 0 2	1 0 0	1 0 4	1 0 2	1 0 1	9 9	1 0 1	1 0 0	9 9	9 8	9 9	9 8	9 7	9 6	9 4	
				7 . 0	1 0 6	1 0 5	1 0 3	1 0 2	1 0 5	1 0 4	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	1 0 1	1 0 0	1 0 0	9 9	9 8	9 6	
				1 0 . 0	1 0 7	1 0 6	1 0 5	1 0 4	1 0 5	1 0 5	1 0 4	1 0 3	1 0 3	1 0 3	1 0 2	1 0 1	1 0 1	1 0 1	1 0 0	1 0 0	9 7	

