

| 屋内照明器具特性 |                                |
|----------|--------------------------------|
| 品番 (品名)  | XND9930FS                      |
| 光源       | LED5000_80_13835 ×1 13835.0 lm |
| 管理番号     | K0164064(0)D 1                 |
| BZ分類     | BZ1                            |

| 器具効率   | 100%                                | 天井       | 80%           |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |    |
|--------|-------------------------------------|----------|---------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|
|        |                                     |          | 壁             | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0% |
| 上方光束   | 0%                                  | 反射率      | 10%           |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0%  |    |
| 下方光束   | 100%                                |          | 床             | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0% |
|        |                                     | 室指数      | 照明率 ( X0.01 ) |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     | ZCM |    |
| 保守率    | 良<br>中<br>否<br>0.72<br>0.68<br>0.64 | 0.6      | 78            | 71  | 67  | 63  | 78  | 71  | 66  | 63  | 76  | 70  | 66  | 63  | 75  | 69  | 66  | 63  | 62  |    |
|        |                                     | 0.8      | 86            | 80  | 75  | 72  | 85  | 79  | 75  | 72  | 83  | 78  | 74  | 72  | 82  | 77  | 74  | 71  | 70  |    |
|        |                                     | 1.0      | 91            | 85  | 81  | 78  | 90  | 84  | 81  | 78  | 88  | 83  | 80  | 77  | 86  | 82  | 79  | 77  | 76  |    |
|        |                                     | 1.25     | 94            | 89  | 86  | 83  | 93  | 89  | 85  | 83  | 91  | 87  | 84  | 82  | 90  | 86  | 84  | 82  | 80  |    |
| 下方投影面積 | c m <sup>2</sup>                    | 1.5      | 97            | 92  | 89  | 86  | 96  | 92  | 88  | 86  | 94  | 90  | 87  | 85  | 92  | 89  | 87  | 85  | 83  |    |
|        |                                     | 2.0      | 100           | 96  | 93  | 91  | 99  | 95  | 93  | 90  | 96  | 94  | 91  | 89  | 95  | 92  | 90  | 89  | 87  |    |
| 取付高さ   | 器具間隔最大限                             |          | 2.5           | 101 | 98  | 96  | 94  | 100 | 98  | 95  | 93  | 98  | 96  | 94  | 92  | 96  | 94  | 93  | 91  | 89 |
|        | 横方向 (A)                             | 縦方向 (B)  | 3.0           | 103 | 100 | 98  | 96  | 101 | 99  | 97  | 95  | 99  | 97  | 96  | 94  | 97  | 96  | 94  | 93  | 91 |
| H m    | 0.98 H m                            | 0.98 H m | 4.0           | 104 | 102 | 100 | 99  | 103 | 101 | 99  | 98  | 101 | 99  | 98  | 97  | 99  | 97  | 96  | 95  | 93 |
|        |                                     |          | 5.0           | 105 | 103 | 102 | 100 | 104 | 102 | 101 | 100 | 102 | 100 | 99  | 98  | 100 | 99  | 98  | 97  | 94 |
|        |                                     |          | 7.0           | 106 | 105 | 104 | 103 | 105 | 104 | 103 | 102 | 103 | 102 | 101 | 100 | 101 | 100 | 99  | 98  | 96 |
|        |                                     |          | 10.0          | 107 | 106 | 105 | 104 | 105 | 105 | 104 | 103 | 103 | 103 | 102 | 101 | 101 | 100 | 100 | 99  | 97 |

