

屋内照明器具特性	
品番(品名)	XND9969WNK
光源	LED5000_80_11655 ×1 11655.0 lm
管理番号	K0155318(0)DB1
BZ分類	BZ1

器具効率	101%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	101%	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否 0.76 0.72 0.64	0.6	78	70	66	62	77	70	65	62	75	69	65	62	74	68	65	62	61	
		0.8	85	78	74	70	84	78	73	70	82	77	73	70	81	76	72	70	68	
		1.0	89	83	79	76	88	83	79	75	86	82	78	75	85	80	77	75	73	
		1.25	93	88	84	80	92	87	83	80	90	86	82	80	88	84	82	79	77	
下方投影面積	c m <sup>2</sup>	1.5	96	91	87	84	94	90	86	83	92	88	85	83	90	87	84	82	80	
		2.0	99	95	91	89	98	94	91	88	95	92	90	87	93	91	88	87	85	
取付高さ	器具間隔最大限		2.5	101	97	94	92	100	96	94	91	97	95	92	90	95	93	91	89	87
	横方向(A)	縦方向(B)	3.0	102	99	96	94	101	98	96	94	99	96	94	92	97	95	93	91	89
H m	1.19H m	1.19H m	4.0	104	101	99	97	103	100	98	97	100	98	97	95	98	97	95	94	92
			5.0	105	103	101	99	104	102	100	99	101	100	98	97	99	98	97	96	93
			7.0	106	105	103	102	105	103	102	101	102	101	100	99	100	99	98	95	
			10.0	107	106	105	104	106	105	104	103	103	103	102	101	101	100	99	97	

