

屋内照明器具特性

品番 (品名)	XLX460NKNP														
光源	LED5000_85_6040 x1 6040.0 1m														
管理番号	K0144286(0)DB1														
BZ分類	BZ4/6.0/BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	10%	反射率	床	10%				10%				10%				10%				0%
下方光束	90%		室指数	照明率 (X0.01) ZCM																
保守率	良	0.83	0.6	58	47	40	35	57	46	39	34	53	44	38	34	50	43	37	33	30
	中	0.81	0.8	68	58	50	45	66	56	50	45	62	54	48	44	59	52	47	43	40
	否	0.77	1.0	75	65	58	53	72	63	57	52	68	61	55	51	65	58	53	49	46
			1.25	80	71	65	60	78	70	64	59	74	67	62	57	70	64	60	56	52
下方投影面積			1.5	84	76	70	65	82	74	68	64	77	71	66	62	73	68	64	60	57
			2.0	89	82	77	72	87	80	75	71	82	77	73	69	78	74	70	67	63
取付高さ	器具間隔最大限		2.5	92	86	81	77	90	84	80	76	85	81	77	74	81	77	74	71	67
	横方向 (A)	縦方向 (B)	3.0	94	89	85	81	92	87	83	80	87	83	80	77	83	80	77	75	70
1.5m	1.95m	2.04m	4.0	97	93	89	86	95	91	88	85	90	87	84	82	86	83	81	79	74
2	2.58	2.58	5.0	99	95	92	89	96	93	90	88	92	89	87	85	87	85	83	82	77
2.5	3.21	3.15	7.0	101	98	96	94	98	96	94	92	94	92	90	88	89	88	86	85	80
3	3.84	3.72	10.0	102	100	99	97	100	98	96	95	95	94	93	91	91	90	89	88	82

