

# 屋内照明器具特性

|         |                    |           |
|---------|--------------------|-----------|
| 品番 (品名) | XND2067 WWK        |           |
| 光源      | LED4000_85_1965 ×1 | 1965.0 lm |
| 管理番号    | K0176638 (0) DB1   |           |
| BZ分類    | BZ1                |           |

| 器具効率   | 100%            | 天井      | 80%  |               |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |    | 0% |     |
|--------|-----------------|---------|------|---------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|-----|
|        |                 |         | 壁    | 70            | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30 | 10 | 0%  |
| 上方光束   | 0%              | 反射率     | 床    | 10%           |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |    |    | 0%  |
| 下方光束   | 100%            |         | 室指数  | 照明率 ( X0.01 ) |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    | ZCM |
| 保守率    | 良               | 0.81    | 0.6  | 72            | 63  | 57  | 54  | 71  | 63  | 57  | 54  | 69  | 62  | 57  | 53  | 67  | 61  | 57 | 53 | 52  |
|        | 中               | 0.77    | 0.8  | 81            | 74  | 69  | 65  | 80  | 73  | 68  | 65  | 78  | 72  | 68  | 64  | 77  | 71  | 67 | 64 | 63  |
|        | 否               | 0.68    | 1.0  | 87            | 80  | 76  | 72  | 86  | 80  | 75  | 72  | 84  | 79  | 75  | 72  | 82  | 77  | 74 | 71 | 70  |
|        |                 |         | 1.25 | 91            | 86  | 81  | 78  | 90  | 85  | 81  | 78  | 88  | 84  | 80  | 77  | 86  | 82  | 79 | 77 | 75  |
| 下方投影面積 | cm <sup>2</sup> |         | 1.5  | 94            | 89  | 85  | 82  | 93  | 88  | 85  | 82  | 91  | 87  | 84  | 81  | 89  | 86  | 83 | 81 | 79  |
| 等価発光面積 | cm <sup>2</sup> |         | 2.0  | 98            | 94  | 90  | 88  | 97  | 93  | 90  | 87  | 94  | 91  | 89  | 86  | 92  | 90  | 88 | 86 | 84  |
| 取付高さ   | 器具間隔最大限         |         | 2.5  | 100           | 97  | 94  | 91  | 99  | 96  | 93  | 91  | 97  | 94  | 92  | 90  | 94  | 92  | 90 | 89 | 87  |
|        | 横方向 (A)         | 縦方向 (B) | 3.0  | 101           | 98  | 96  | 94  | 100 | 97  | 95  | 93  | 98  | 96  | 94  | 92  | 96  | 94  | 92 | 91 | 89  |
| Hm     | 1.25Hm          | 1.25Hm  | 4.0  | 103           | 101 | 99  | 97  | 102 | 100 | 98  | 96  | 100 | 98  | 96  | 95  | 98  | 96  | 95 | 94 | 91  |
|        |                 |         | 5.0  | 104           | 102 | 101 | 99  | 103 | 101 | 100 | 98  | 101 | 99  | 98  | 97  | 99  | 97  | 96 | 95 | 93  |
|        |                 |         | 7.0  | 105           | 104 | 103 | 101 | 104 | 103 | 102 | 101 | 102 | 101 | 100 | 99  | 100 | 99  | 98 | 97 | 95  |
|        |                 |         | 10.0 | 106           | 105 | 104 | 103 | 105 | 104 | 103 | 102 | 103 | 102 | 101 | 101 | 100 | 100 | 99 | 99 | 96  |

