

屋内照明器具特性	
品番 (品名)	XND1058WNK
光源	LED5000_85_1010 x1 1010.0lm
管理番号	K0176472 (0) DB1
BZ分類	BZ1

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		0 %	室指数	照明率 (X0.01)																			Z	C	M
下方光束		100 %																							
保守率		良	0.81	0.6	85	79	76	73	85	79	76	73	83	79	75	73	82	78	75	73	72				
		中	0.77	0.8	91	86	82	80	90	86	82	80	89	85	82	80	88	84	81	79	78				
		否	0.68	1.0	95	90	87	84	94	90	87	84	92	89	86	84	91	88	85	84	82				
				1.25	98	94	91	88	97	93	90	88	95	92	90	88	93	91	89	87	86				
下方投影面積		c m ²	1.5	99	96	93	91	99	95	93	91	97	94	92	90	95	93	91	89	88					
等価発光面積			c m ²	2.0	102	99	97	95	101	98	96	94	99	97	95	93	97	95	94	93	91				
取付	器具間隔最大限			2.5	103	101	99	97	102	100	98	97	100	98	97	95	98	97	96	94	93				
高さ	横方向 (A)		縦方向 (B)	3.0	104	102	100	99	103	101	100	98	101	100	98	97	99	98	97	96	94				
H m	0.75 H m		0.75 H m	4.0	105	104	102	101	104	103	101	100	102	101	100	99	100	99	98	98	95				
				5.0	106	105	103	102	105	104	103	102	103	102	101	100	101	100	99	99	96				
				7.0	107	106	105	104	106	105	104	103	104	103	102	101	101	100	100	100	97				
				10.0	107	107	106	105	106	106	105	104	104	104	103	103	102	102	101	101	98				

