

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | XNW3 5 8 0 WW                |
| 光源       | LED4000_85_3690 x1 3690.0 lm |
| 管理番号     | K0164308 ( 0 ) DB 1          |
| BZ分類     | BZ1                          |

| 器具効率     |           | 100 %            | 反射率    | 天井            | 80 %             |     |     |     | 70 % |     |     |     | 50 % |     |     |     | 30 % |     |    |    | 0 % |    |    |   |   |  |   |
|----------|-----------|------------------|--------|---------------|------------------|-----|-----|-----|------|-----|-----|-----|------|-----|-----|-----|------|-----|----|----|-----|----|----|---|---|--|---|
|          |           |                  |        | 壁             | 70               | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30 | 10 | 0 % |    |    |   |   |  |   |
|          |           |                  |        | 床             | 10 %             |     |     |     | 10 % |     |     |     | 10 % |     |     |     | 10 % |     |    |    | 0 % |    |    |   |   |  |   |
| 上方光束     |           | 0 %              | 室指数    | 照明率 ( X0.01 ) |                  |     |     |     |      |     |     |     |      |     |     |     |      |     |    |    |     |    |    | Z | C |  | M |
| 下方光束     |           | 100 %            |        |               |                  |     |     |     |      |     |     |     |      |     |     |     |      |     |    |    |     |    |    |   |   |  |   |
| 保守率      |           | 良<br>中<br>否      | 0.81   | 0.6           | 75               | 67  | 62  | 59  | 75   | 67  | 62  | 59  | 73   | 66  | 62  | 59  | 71   | 65  | 61 | 58 | 57  |    |    |   |   |  |   |
|          |           |                  | 0.77   | 0.8           | 84               | 77  | 72  | 68  | 83   | 76  | 71  | 68  | 81   | 75  | 71  | 68  | 79   | 74  | 70 | 68 | 66  |    |    |   |   |  |   |
|          |           |                  | 0.68   | 1.0           | 89               | 82  | 78  | 74  | 88   | 82  | 77  | 74  | 86   | 81  | 77  | 74  | 84   | 79  | 76 | 73 | 72  |    |    |   |   |  |   |
|          |           |                  |        | 1.25          | 93               | 87  | 83  | 80  | 92   | 87  | 83  | 80  | 90   | 85  | 82  | 79  | 88   | 84  | 81 | 79 | 77  |    |    |   |   |  |   |
| 下方投影面積   |           | c m <sup>2</sup> |        | 1.5           | 96               | 91  | 87  | 84  | 94   | 90  | 86  | 84  | 92   | 88  | 85  | 83  | 90   | 87  | 84 | 82 | 81  |    |    |   |   |  |   |
|          |           |                  | 等価発光面積 |               | c m <sup>2</sup> | 2.0 | 99  | 95  | 92   | 89  | 98  | 94  | 91   | 89  | 96  | 93  | 90   | 88  | 94 | 91 | 89  | 87 | 85 |   |   |  |   |
| 取付<br>高さ | 器具間隔最大限   |                  | 2.5    | 101           | 98               | 95  | 92  | 100 | 97   | 94  | 92  | 98  | 95   | 93  | 91  | 96  | 93   | 92  | 90 | 88 |     |    |    |   |   |  |   |
|          | 横方向 ( A ) | 縦方向 ( B )        | 3.0    | 102           | 99               | 97  | 95  | 101 | 98   | 96  | 94  | 99  | 97   | 95  | 93  | 97  | 95   | 93  | 92 | 90 |     |    |    |   |   |  |   |
| H m      | 0.74 H m  | 0.74 H m         | 4.0    | 104           | 102              | 100 | 98  | 103 | 101  | 99  | 97  | 100 | 99   | 97  | 96  | 98  | 97   | 96  | 95 | 92 |     |    |    |   |   |  |   |
|          |           |                  | 5.0    | 105           | 103              | 101 | 100 | 104 | 102  | 101 | 99  | 101 | 100  | 99  | 98  | 99  | 98   | 97  | 96 | 94 |     |    |    |   |   |  |   |
|          |           |                  | 7.0    | 106           | 105              | 103 | 102 | 105 | 104  | 102 | 101 | 103 | 102  | 101 | 100 | 100 | 100  | 99  | 98 | 95 |     |    |    |   |   |  |   |
|          |           |                  | 10.0   | 107           | 106              | 105 | 104 | 106 | 105  | 104 | 103 | 103 | 103  | 102 | 101 | 101 | 101  | 100 | 99 | 97 |     |    |    |   |   |  |   |

