

屋内照明器具特性	
品番 (品名)	XND1067WVK
光源	LED3500_85_980 x1 980.0 lm
管理番号	K0176638 (0) DB1
BZ分類	BZ1

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.81	0.6	72	63	57	54	71	63	57	54	69	62	57	53	67	61	57	53	52
			0.77	0.8	81	74	69	65	80	73	68	65	78	72	68	64	77	71	67	64	63
			0.68	1.0	87	80	76	72	86	80	75	72	84	79	75	72	82	77	74	71	70
				1.25	91	86	81	78	90	85	81	78	88	84	80	77	86	82	79	77	75
下方投影面積 等価発光面積		cm ²		1.5	94	89	85	82	93	88	85	82	91	87	84	81	89	86	83	81	79
				2.0	98	94	90	88	97	93	90	87	94	91	89	86	92	90	88	86	84
取付 高さ	器具間隔最大限		2.5	100	97	94	91	99	96	93	91	97	94	92	90	94	92	90	89	87	
	横方向 (A) 縦方向 (B)			3.0	101	98	96	94	100	97	95	93	98	96	94	92	96	94	92	91	89
H m	1.25 H m	1.25 H m	4.0	103	101	99	97	102	100	98	96	100	98	96	95	98	96	95	94	91	
			5.0	104	102	101	99	103	101	100	98	101	99	98	97	99	97	96	95	93	
			7.0	105	104	103	101	104	103	102	101	102	101	100	99	100	99	98	97	95	
			10.0	106	105	104	103	105	104	103	102	103	102	101	101	100	99	99	99	96	

