

# 屋内照明器具特性

品番 (品名)	XNN3556SW	
光源	LED4000_80_3905 ×1	3905.0lm
管理番号	K0179567(0)DB1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%																							
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10																								
上方光束	0%	反射率	照明率 (X0.01)																				ZCM																			
下方光束	100%	室指数																																								
保守率	良 0.76	0.6	79	72	67	64	78	72	67	64	77	71	67	64	75	70	67	64	63	79	72	67	64	78	72	67	64	77	71	67	64	75	70	67	64	63						
	中 0.72	0.8	87	80	76	73	86	80	76	73	84	79	75	73	83	78	75	72	71	87	80	76	73	86	80	76	73	84	79	75	73	83	78	75	72	71						
	否 0.64	1.0	91	86	82	79	90	85	81	79	89	84	81	78	87	83	80	78	76	91	86	82	79	90	85	81	79	89	84	81	78	87	83	80	78	76						
下方投影面積	cm <sup>2</sup>	1.25	95	90	86	84	94	89	86	83	92	88	85	83	90	87	84	82	81	95	90	86	84	94	89	86	83	92	88	85	83	90	87	84	82	81						
		1.5	97	93	90	87	96	92	89	87	94	91	88	86	92	90	87	85	84	97	93	90	87	96	92	89	87	94	91	88	86	92	90	87	85	84						
等価発光面積	cm <sup>2</sup>	2.0	100	97	94	92	99	96	93	91	97	94	92	90	95	93	91	90	88	100	97	94	92	99	96	93	91	97	94	92	90	95	93	91	90	88						
		2.5	102	99	97	95	101	98	96	94	99	97	95	93	97	95	93	92	90	102	99	97	95	101	98	96	94	99	97	95	93	97	95	93	92	90						
取付高さ	器具間隔最大限		3.0	103	101	98	97	102	100	98	96	100	98	96	95	98	96	95	94	92	103	101	98	97	102	100	98	96	100	98	96	95	98	96	95	94	92					
	Hm	0.72Hm	0.72Hm	4.0	104	103	101	99	103	102	100	99	101	100	98	97	99	98	97	96	94	104	103	101	99	103	102	100	99	101	100	98	97	99	98	97	96	94				
			5.0	105	104	102	101	104	103	101	100	102	101	100	99	100	99	98	97	95	105	104	102	101	104	103	101	100	102	101	100	99	100	99	98	97	95					
			7.0	106	105	104	103	105	104	103	102	103	102	101	100	101	100	99	99	96	106	105	104	103	105	104	103	102	103	102	101	100	101	100	99	99	96					
			10.0	107	106	105	105	106	105	104	104	104	103	102	102	101	101	100	100	97	107	106	105	105	106	105	104	104	104	103	102	102	101	101	100	100	97					

