

| 屋内照明器具特性 |                             |
|----------|-----------------------------|
| 品番 (品名)  | XND2536WEK                  |
| 光源       | LED3000_85_1810 x1 1810.0lm |
| 管理番号     | K0176630(0)DB1              |
| BZ分類     | BZ1                         |

| 器具効率     |           | 101 %            | 反射率       | 天井            | 80 %             |     |     |     | 70 % |     |     |     | 50 % |     |     |     | 30 % |     |     |     | 0 % |    |     |  |
|----------|-----------|------------------|-----------|---------------|------------------|-----|-----|-----|------|-----|-----|-----|------|-----|-----|-----|------|-----|-----|-----|-----|----|-----|--|
|          |           |                  |           | 壁             | 70               | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 0 % |    |     |  |
|          |           |                  |           | 床             | 10 %             |     |     |     | 10 % |     |     |     | 10 % |     |     |     | 10 % |     |     |     | 0 % |    |     |  |
| 上方光束     |           | 0 %              | 室指数       | 照明率 ( X0.01 ) |                  |     |     |     |      |     |     |     |      |     |     |     |      |     |     |     |     |    | ZCM |  |
| 下方光束     |           | 101 %            |           |               |                  |     |     |     |      |     |     |     |      |     |     |     |      |     |     |     |     |    |     |  |
| 保守率      |           | 良<br>中<br>否      | 0.6       | 88            | 82               | 79  | 77  | 87  | 82   | 79  | 77  | 86  | 81   | 79  | 76  | 85  | 81   | 78  | 76  | 75  |     |    |     |  |
|          |           |                  | 0.77      | 93            | 88               | 85  | 83  | 92  | 88   | 85  | 83  | 91  | 87   | 85  | 83  | 90  | 87   | 84  | 82  | 81  |     |    |     |  |
|          |           |                  | 1.0       | 96            | 92               | 89  | 87  | 96  | 92   | 89  | 87  | 94  | 91   | 88  | 87  | 93  | 90   | 88  | 86  | 85  |     |    |     |  |
|          |           |                  | 0.68      | 1.25          | 99               | 95  | 93  | 91  | 98   | 95  | 92  | 90  | 97   | 94  | 92  | 90  | 95   | 93  | 91  | 89  | 88  |    |     |  |
| 下方投影面積   |           | c m <sup>2</sup> | 1.5       | 101           | 98               | 95  | 93  | 100 | 97   | 95  | 93  | 98  | 96   | 94  | 92  | 97  | 94   | 93  | 91  | 90  |     |    |     |  |
|          |           |                  | 等価発光面積    |               | c m <sup>2</sup> | 2.0 | 103 | 100 | 98   | 96  | 102 | 99  | 98   | 96  | 100 | 98  | 96   | 95  | 98  | 97  | 95  | 94 | 92  |  |
| 取付<br>高さ | 器具間隔最大限   |                  | 2.5       | 104           | 102              | 100 | 98  | 103 | 101  | 99  | 98  | 101 | 100  | 98  | 97  | 99  | 98   | 97  | 96  | 94  |     |    |     |  |
|          | 横方向 ( A ) |                  | 縦方向 ( B ) |               | 3.0              | 105 | 103 | 101 | 100  | 104 | 102 | 101 | 99   | 102 | 101 | 99  | 98   | 100 | 99  | 98  | 97  | 95 |     |  |
| H m      | 0.76 H m  |                  | 0.76 H m  |               | 4.0              | 106 | 104 | 103 | 102  | 105 | 104 | 103 | 102  | 101 | 100 | 101 | 100  | 99  | 98  | 96  |     |    |     |  |
|          |           |                  |           |               | 5.0              | 107 | 105 | 104 | 103  | 105 | 104 | 103 | 102  | 103 | 103 | 102 | 101  | 101 | 100 | 99  | 97  |    |     |  |
|          |           |                  |           |               | 7.0              | 107 | 106 | 106 | 105  | 106 | 105 | 105 | 104  | 104 | 103 | 103 | 102  | 102 | 101 | 101 | 98  |    |     |  |
|          |           |                  |           |               | 10.0             | 108 | 107 | 107 | 106  | 107 | 106 | 106 | 105  | 104 | 104 | 104 | 103  | 102 | 102 | 101 | 99  |    |     |  |

