

屋内照明器具特性	
品番 (品名)	XNW3 5 8 0 WV
光源	LED3500_85_3660 x1 3660.0 lm
管理番号	K0164308 (0) DB 1
BZ分類	BZ1

器具効率		1 0 0 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %				
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %				
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																				Z C M	
下方光束		1 0 0 %																							
保守率		良 中 否	0 . 6	7 5	6 7	6 2	5 9	7 5	6 7	6 2	5 9	7 3	6 6	6 2	5 9	7 1	6 5	6 1	5 8	5 7					
			0 . 8	8 4	7 7	7 2	6 8	8 3	7 6	7 1	6 8	8 1	7 5	7 1	6 8	7 9	7 4	7 0	6 8	6 6					
			1 . 0	8 9	8 2	7 8	7 4	8 8	8 2	7 7	7 4	8 6	8 1	7 7	7 4	8 4	7 9	7 6	7 3	7 2					
			0 . 6 8	1 . 2 5	9 3	8 7	8 3	8 0	9 2	8 7	8 3	8 0	9 0	8 5	8 2	7 9	8 8	8 4	8 1	7 9	7 7				
下方投影面積		c m ²	1 . 5	9 6	9 1	8 7	8 4	9 4	9 0	8 6	8 4	9 2	8 8	8 5	8 3	9 0	8 7	8 4	8 2	8 1					
			2 . 0	9 9	9 5	9 2	8 9	9 8	9 4	9 1	8 9	9 6	9 3	9 0	8 8	9 4	9 1	8 9	8 7	8 5					
取付 高さ	器具間隔最大限		2 . 5	1 0 1	9 8	9 5	9 2	1 0 0	9 7	9 4	9 2	9 8	9 5	9 3	9 1	9 6	9 3	9 2	9 0	8 8					
	横方向 (A)		縦方向 (B)		3 . 0	1 0 2	9 9	9 7	9 5	1 0 1	9 8	9 6	9 4	9 9	9 7	9 5	9 3	9 7	9 5	9 3	9 2	9 0			
H m	0 . 7 4 H m		0 . 7 4 H m		4 . 0	1 0 4	1 0 2	1 0 0	9 8	1 0 3	1 0 1	9 9	9 7	1 0 0	9 9	9 7	9 6	9 8	9 7	9 6	9 5	9 2			
					5 . 0	1 0 5	1 0 3	1 0 1	1 0 0	1 0 4	1 0 2	1 0 1	9 9	1 0 1	1 0 0	9 9	9 8	9 9	9 8	9 7	9 6	9 4			
					7 . 0	1 0 6	1 0 5	1 0 3	1 0 2	1 0 5	1 0 4	1 0 2	1 0 1	1 0 3	1 0 2	1 0 1	1 0 0	1 0 0	1 0 0	9 9	9 8	9 5			
					1 0 . 0	1 0 7	1 0 6	1 0 5	1 0 4	1 0 6	1 0 5	1 0 4	1 0 3	1 0 3	1 0 3	1 0 2	1 0 1	1 0 1	1 0 1	1 0 0	9 9	9 7			

