

屋内照明器具特性

品番 (品名)	XND2538WNK	
光源	LED5000_85_2400 ×1	2400.0lm
管理番号	K0176468(0)DB1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束		0%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	100%	床	10%				10%				10%				10%				0%	
室指数			照明率 (X0.01)																ZCM	
保守率	良	0.81	0.6	86	80	76	74	85	80	76	74	84	79	76	74	83	78	76	73	72
	中	0.77	0.8	91	86	83	81	91	86	83	80	89	85	82	80	88	84	82	80	79
	否	0.68	1.0	95	91	87	85	94	90	87	85	93	89	86	84	91	88	86	84	83
下方投影面積	等価発光面積	cm ²	1.25	98	94	91	89	97	93	91	88	95	92	90	88	94	91	89	87	86
			1.5	100	96	93	91	99	96	93	91	97	94	92	90	95	93	91	90	88
取付高さ	器具間隔最大限		2.0	102	99	97	95	101	98	96	94	99	97	95	94	97	96	94	93	91
	横方向 (A)	縦方向 (B)	2.5	103	101	99	97	102	100	98	97	100	99	97	96	99	97	96	95	93
Hm	0.75Hm	0.75Hm	3.0	104	102	100	99	103	101	100	98	101	100	98	97	99	98	97	96	94
			4.0	105	104	102	101	104	103	101	100	102	101	100	99	100	99	98	98	95
			5.0	106	105	103	102	105	104	103	102	103	102	101	100	101	100	99	99	96
			7.0	107	106	105	104	106	105	104	103	103	103	102	101	101	101	100	100	97
			10.0	107	107	106	105	106	106	105	104	104	103	103	103	102	102	101	101	98

