

屋内照明器具特性	
品番 (品名)	XND2558SV
光源	LED3500_85_2360 x1 2360.0lm
管理番号	K0176473(0)DB1
BZ分類	BZ1

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		0 %	室指数	照明率 (X0.01)																		Z	C		M
下方光束		100 %																							
保守率		良	0.81	0.6	77	70	65	61	76	69	65	61	75	68	64	61	73	68	64	61	60				
		中	0.77	0.8	85	79	74	71	84	78	74	70	82	77	73	70	81	76	73	70	69				
		否	0.68	1.0	90	84	80	77	89	84	80	76	87	82	79	76	85	81	78	76	74				
				1.25	94	89	85	82	93	88	84	82	91	87	84	81	89	86	83	81	79				
下方投影面積		c m ²		1.5	97	92	88	86	95	91	88	85	93	90	87	85	92	89	86	84	82				
等価発光面積		c m ²		2.0	100	96	93	91	99	95	92	90	96	94	91	89	95	92	90	88	87				
取付高さ	器具間隔最大限			2.5	102	98	96	94	100	98	95	93	98	96	94	92	96	94	93	91	89				
	横方向 (A)		縦方向 (B)	3.0	103	100	98	96	102	99	97	95	99	97	96	94	97	96	94	93	91				
H m	0.75 H m		0.75 H m	4.0	104	102	100	99	103	101	100	98	101	99	98	97	99	98	96	95	93				
				5.0	105	103	102	101	104	102	101	100	102	101	99	98	100	99	98	97	94				
				7.0	106	105	104	103	105	104	103	102	103	102	101	100	101	100	99	99	96				
				10.0	107	106	105	104	106	105	104	103	104	103	102	101	101	100	100	99	97				

