

# 屋内照明器具特性

品番 (品名) XND9978SWK

光源 LED4000\_80\_15400 x1 15400.0 1m

管理番号 K0155308(0)DB1

BZ分類 BZ1

| 器具効率             | 100%            | 天井              | 80%           |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |    |
|------------------|-----------------|-----------------|---------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|
|                  |                 |                 | 70            | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  |     |    |
| 上方光束             | 0%              | 反射率             | 壁             |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |
| 下方光束             | 100%            |                 | 床             | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     |    |
|                  |                 | 室指数             | 照明率 ( X0.01 ) |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     | ZCM |    |
| 保守率              | 良               | 0.76            | 0.6           | 80  | 73  | 69  | 66  | 79  | 73  | 69  | 66  | 78  | 72  | 68  | 66  | 77  | 72  | 68  | 65  | 64 |
|                  | 中               | 0.72            | 0.8           | 88  | 82  | 77  | 74  | 87  | 81  | 77  | 74  | 85  | 80  | 77  | 74  | 84  | 79  | 76  | 74  | 72 |
|                  | 否               | 0.64            | 1.0           | 92  | 87  | 83  | 80  | 91  | 86  | 82  | 80  | 89  | 85  | 82  | 79  | 88  | 84  | 81  | 79  | 78 |
| 下方投影面積<br>等価発光面積 | cm <sup>2</sup> | cm <sup>2</sup> | 1.25          | 95  | 91  | 87  | 85  | 94  | 90  | 87  | 84  | 93  | 89  | 86  | 84  | 91  | 88  | 85  | 83  | 82 |
|                  |                 |                 | 1.5           | 98  | 94  | 90  | 88  | 97  | 93  | 90  | 88  | 95  | 92  | 89  | 87  | 93  | 90  | 88  | 86  | 85 |
|                  |                 |                 | 2.0           | 101 | 97  | 94  | 92  | 99  | 96  | 94  | 92  | 97  | 95  | 93  | 91  | 96  | 93  | 92  | 90  | 88 |
| 取付高さ             | 器具間隔最大限         |                 | 2.5           | 102 | 99  | 97  | 95  | 101 | 99  | 96  | 95  | 99  | 97  | 95  | 93  | 97  | 95  | 94  | 92  | 91 |
|                  | 横方向 (A)         | 縦方向 (B)         | 3.0           | 103 | 101 | 99  | 97  | 102 | 100 | 98  | 96  | 100 | 98  | 97  | 95  | 98  | 97  | 95  | 94  | 92 |
| Hm               | 0.64Hm          | 0.64Hm          | 4.0           | 105 | 103 | 101 | 100 | 103 | 102 | 100 | 99  | 101 | 100 | 99  | 98  | 99  | 98  | 97  | 96  | 94 |
|                  |                 |                 | 5.0           | 105 | 104 | 103 | 101 | 104 | 103 | 102 | 100 | 102 | 101 | 100 | 99  | 100 | 99  | 98  | 98  | 95 |
|                  |                 |                 | 7.0           | 106 | 105 | 104 | 103 | 105 | 104 | 103 | 102 | 103 | 102 | 101 | 101 | 100 | 100 | 99  | 99  | 96 |
|                  |                 |                 | 10.0          | 107 | 106 | 105 | 105 | 106 | 105 | 104 | 104 | 104 | 103 | 102 | 102 | 101 | 101 | 100 | 100 | 97 |

