

|          |                                |
|----------|--------------------------------|
| 屋内照明器具特性 |                                |
| 品番 (品名)  | XND9979WLK                     |
| 光源       | LED3000_80_14910 ×1 14910.0 lm |
| 管理番号     | K0155312(0)DB1                 |
| BZ分類     | BZ1                            |

|        |         |                 |             |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |
|--------|---------|-----------------|-------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|
| 器具効率   | 100%    | 天井              | 80%         |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |    |
|        |         | 壁               | 70          | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0%  |    |
| 上方光束   | 0%      | 床               | 10%         |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0%  |    |
| 下方光束   | 100%    | 室指数             | 照明率 (X0.01) |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     | ZCM |    |
| 保守率    | 良       | 0.76            | 0.6         | 78  | 71  | 66  | 62  | 77  | 70  | 66  | 62  | 76  | 69  | 65  | 62  | 74  | 69  | 65  | 62  | 61 |
|        | 中       | 0.72            | 0.8         | 85  | 78  | 74  | 70  | 84  | 78  | 73  | 70  | 82  | 77  | 73  | 70  | 81  | 76  | 72  | 70  | 68 |
|        | 否       | 0.64            | 1.0         | 89  | 83  | 79  | 76  | 88  | 83  | 79  | 75  | 86  | 82  | 78  | 75  | 85  | 80  | 77  | 75  | 73 |
|        |         |                 | 1.25        | 93  | 88  | 84  | 80  | 92  | 87  | 83  | 80  | 90  | 86  | 82  | 80  | 88  | 84  | 82  | 79  | 78 |
| 下方投影面積 |         | cm <sup>2</sup> | 1.5         | 96  | 91  | 87  | 84  | 94  | 90  | 86  | 83  | 92  | 88  | 85  | 83  | 90  | 87  | 84  | 82  | 80 |
| 等価発光面積 |         | cm <sup>2</sup> | 2.0         | 99  | 95  | 91  | 89  | 98  | 94  | 91  | 88  | 95  | 92  | 90  | 87  | 93  | 91  | 88  | 86  | 85 |
| 取付高さ   | 器具間隔最大限 |                 | 2.5         | 101 | 97  | 94  | 92  | 99  | 96  | 94  | 91  | 97  | 95  | 92  | 90  | 95  | 93  | 91  | 89  | 87 |
|        | 横方向 (A) | 縦方向 (B)         | 3.0         | 102 | 99  | 96  | 94  | 101 | 98  | 96  | 94  | 98  | 96  | 94  | 92  | 96  | 94  | 93  | 91  | 89 |
| Hm     | 1.16Hm  | 1.16Hm          | 4.0         | 104 | 101 | 99  | 97  | 102 | 100 | 98  | 97  | 100 | 98  | 97  | 95  | 98  | 96  | 95  | 94  | 92 |
|        |         |                 | 5.0         | 105 | 103 | 101 | 99  | 103 | 102 | 100 | 99  | 101 | 100 | 98  | 97  | 99  | 98  | 97  | 96  | 93 |
|        |         |                 | 7.0         | 106 | 104 | 103 | 102 | 105 | 103 | 102 | 101 | 102 | 101 | 100 | 99  | 100 | 99  | 98  | 98  | 95 |
|        |         |                 | 10.0        | 107 | 106 | 105 | 104 | 105 | 104 | 104 | 103 | 103 | 102 | 102 | 101 | 101 | 100 | 100 | 99  | 96 |

