

| 屋内照明器具特性 |                            |
|----------|----------------------------|
| 品番 (品名)  | XND0657SV                  |
| 光源       | LED3500_85_580 ×1 580.0 lm |
| 管理番号     | K0176637 (0) DB1           |
| BZ分類     | BZ1                        |

| 器具効率     |           | 100 %           | 反射率  | 天井            | 80 % |     |     |     | 70 % |     |     |     | 50 % |     |     |     | 30 % |     |    |    | 0 % |  |   |    |
|----------|-----------|-----------------|------|---------------|------|-----|-----|-----|------|-----|-----|-----|------|-----|-----|-----|------|-----|----|----|-----|--|---|----|
|          |           |                 |      | 壁             | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30 | 10 | 0 % |  |   |    |
|          |           |                 |      | 床             | 10 % |     |     |     | 10 % |     |     |     | 10 % |     |     |     | 10 % |     |    |    | 0 % |  |   |    |
| 上方光束     |           | 0 %             | 室指数  | 照明率 ( X0.01 ) |      |     |     |     |      |     |     |     |      |     |     |     |      |     |    |    |     |  | Z | CM |
| 下方光束     |           | 100 %           |      |               |      |     |     |     |      |     |     |     |      |     |     |     |      |     |    |    |     |  |   |    |
| 保守率      |           | 良<br>中<br>否     | 0.81 | 0.6           | 74   | 66  | 60  | 57  | 73   | 65  | 60  | 57  | 71   | 64  | 60  | 56  | 70   | 64  | 59 | 56 | 55  |  |   |    |
|          |           |                 | 0.77 | 0.8           | 83   | 76  | 71  | 68  | 82   | 75  | 71  | 67  | 80   | 74  | 70  | 67  | 79   | 74  | 70 | 67 | 66  |  |   |    |
|          |           |                 | 0.68 | 1.0           | 89   | 82  | 78  | 75  | 88   | 82  | 78  | 74  | 86   | 81  | 77  | 74  | 84   | 80  | 76 | 74 | 72  |  |   |    |
|          |           |                 |      | 1.25          | 93   | 87  | 83  | 80  | 92   | 87  | 83  | 80  | 90   | 86  | 82  | 80  | 88   | 84  | 81 | 79 | 77  |  |   |    |
| 下方投影面積   |           | cm <sup>2</sup> | 1.5  | 95            | 91   | 87  | 84  | 94  | 90   | 87  | 84  | 92  | 89   | 86  | 83  | 90  | 87   | 85  | 83 | 81 |     |  |   |    |
| 等価発光面積   |           | cm <sup>2</sup> | 2.0  | 99            | 95   | 92  | 89  | 98  | 94   | 91  | 89  | 96  | 93   | 90  | 88  | 94  | 91   | 89  | 87 | 85 |     |  |   |    |
| 取付<br>高さ | 器具間隔最大限   |                 | 2.5  | 101           | 98   | 95  | 93  | 100 | 97   | 94  | 92  | 97  | 95   | 93  | 91  | 95  | 93   | 92  | 90 | 88 |     |  |   |    |
|          | 横方向 ( A ) | 縦方向 ( B )       | 3.0  | 102           | 99   | 97  | 95  | 101 | 98   | 96  | 94  | 99  | 97   | 95  | 93  | 97  | 95   | 93  | 92 | 90 |     |  |   |    |
| H m      | 1.05 H m  | 1.05 H m        | 4.0  | 104           | 101  | 100 | 98  | 102 | 101  | 99  | 97  | 100 | 99   | 97  | 96  | 98  | 97   | 96  | 95 | 92 |     |  |   |    |
|          |           |                 | 5.0  | 105           | 103  | 101 | 100 | 103 | 102  | 100 | 99  | 101 | 100  | 99  | 98  | 99  | 98   | 97  | 96 | 94 |     |  |   |    |
|          |           |                 | 7.0  | 106           | 104  | 103 | 102 | 104 | 103  | 102 | 101 | 102 | 101  | 100 | 100 | 100 | 99   | 99  | 98 | 95 |     |  |   |    |
|          |           |                 | 10.0 | 106           | 105  | 105 | 104 | 105 | 104  | 104 | 103 | 103 | 102  | 102 | 101 | 101 | 100  | 100 | 99 | 97 |     |  |   |    |

