

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | XNW2 0 6 1 WV                |
| 光源       | LED3500_85_1805 ×1 1805.0 lm |
| 管理番号     | K0164324 ( 0 ) DB 1          |
| BZ分類     | BZ1                          |

| 器具効率         |                 | 100 %           | 反射率  | 天井                | 80 % |     |     |     |     | 70 % |     |     |     | 50 % |     |     |     | 30 % |    |    |     | 0 % |
|--------------|-----------------|-----------------|------|-------------------|------|-----|-----|-----|-----|------|-----|-----|-----|------|-----|-----|-----|------|----|----|-----|-----|
|              |                 |                 |      | 壁                 | 70   | 50  | 30  | 10  | 70  | 50   | 30  | 10  | 70  | 50   | 30  | 10  | 70  | 50   | 30 | 10 | 0 % |     |
|              |                 |                 |      | 床                 | 10 % |     |     |     |     | 10 % |     |     |     | 10 % |     |     |     | 10 % |    |    |     | 0 % |
| 上方光束<br>下方光束 |                 | 100 %           | 室指数  | 照明率 ( X0.01 ) ZCM |      |     |     |     |     |      |     |     |     |      |     |     |     |      |    |    |     |     |
| 保守率          |                 | 良<br>中<br>否     | 0.81 | 0.6               | 73   | 64  | 59  | 55  | 72  | 64   | 59  | 55  | 70  | 63   | 58  | 55  | 69  | 62   | 58 | 55 | 53  |     |
|              |                 |                 | 0.77 | 0.8               | 82   | 75  | 70  | 66  | 81  | 74   | 69  | 66  | 79  | 73   | 69  | 65  | 77  | 72   | 68 | 65 | 64  |     |
|              |                 |                 | 1.0  | 88                | 81   | 76  | 73  | 87  | 80  | 76   | 73  | 85  | 79  | 75   | 72  | 83  | 78  | 75   | 72 | 70 |     |     |
|              |                 |                 | 0.68 | 1.25              | 92   | 86  | 82  | 79  | 91  | 86   | 82  | 78  | 89  | 84   | 81  | 78  | 87  | 83   | 80 | 77 | 76  |     |
| 下方投影面積       |                 | cm <sup>2</sup> | 1.5  | 95                | 90   | 86  | 83  | 94  | 89  | 85   | 82  | 92  | 88  | 84   | 82  | 90  | 86  | 83   | 81 | 79 |     |     |
| 等価発光面積       |                 |                 | 2.0  | 98                | 94   | 91  | 88  | 97  | 93  | 90   | 88  | 95  | 92  | 89   | 87  | 93  | 90  | 88   | 86 | 84 |     |     |
| 取付<br>高さ     | 器具間隔最大限         |                 | 2.5  | 100               | 97   | 94  | 92  | 99  | 96  | 94   | 91  | 97  | 94  | 92   | 90  | 95  | 93  | 91   | 89 | 87 |     |     |
|              | 横方向 (A) 縦方向 (B) |                 | 3.0  | 102               | 99   | 96  | 94  | 101 | 98  | 96   | 94  | 98  | 96  | 94   | 92  | 96  | 94  | 93   | 91 | 89 |     |     |
| H m          | 1.25 H m        | 1.25 H m        | 4.0  | 104               | 101  | 99  | 97  | 102 | 100 | 98   | 97  | 100 | 98  | 97   | 95  | 98  | 97  | 95   | 94 | 92 |     |     |
|              |                 |                 | 5.0  | 105               | 103  | 101 | 99  | 103 | 102 | 100  | 99  | 101 | 100 | 98   | 97  | 99  | 98  | 97   | 96 | 93 |     |     |
|              |                 |                 | 7.0  | 106               | 104  | 103 | 102 | 104 | 103 | 102  | 101 | 102 | 101 | 100  | 99  | 100 | 99  | 98   | 98 | 95 |     |     |
|              |                 |                 | 10.0 | 106               | 106  | 105 | 104 | 105 | 104 | 104  | 103 | 103 | 102 | 102  | 101 | 101 | 100 | 100  | 99 | 96 |     |     |

